5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	SF 047017-B 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other well other	Angel Peak 9. WELL NO.
2. NAME OF OPERATOR	24
Union Texas Petroleum Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Wildcat Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Box 808, Farmington, New Mexico 87499	AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 12, T28N, R11W, N.M.P.M.
below.) AT SURFACE: 1750 ft./S; 1980 ft./W line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	San Juan New Mexico
AT TOTAL DEPTH: Same as above	14. APL NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	DELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DATA REPORT, OR OTHER DATA SUBSEQUENT REPORT SUBSE	Selevations (show DF, KDB, AND WD) 5747 R.K.B.
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SUBSEQUENT BEFOR OF SUBSEQUENT BEFOR OF	1083
TEST WATER SHUT-OFF FRACTURE TREAT	CICKNOTENREPORT results of Discontinuity of Zolle E
SHOOT OR ACIDIZE	CICHARDEN Report results of Discorden de Zone E
REPAIR WELL	GCNOTENReport results of number place on the place of the
PULL OR ALTER CASING GEOLEMAN MULTIPLE COMPLETE WILL SARMIN	GT.
CHANGE ZONES	
ABANDON*	OON. DN.
CONTRACTOR OPERATIONS (Clearly state all pertinent details, and give pertinent dates,	
including estimated date of starting any proposed work. If well is to measured and true vertical depths for all markers and zones pertine	nt to this work.)*
1. Drilled 9-7/8" hole with mud to intermediate	te total depth of 5348 ft. R.K.B.
2. Ran 126 joints of 7-5/8", 26.40#, K-55 cast	ing and set at 5348 ft. R.K.B. with
stage tool at 2024 ft	
3. Cemented first stage with 1624 cu. ft. of (Flocele per sack, 12.5 lb. of gilsonite per	cook and 118 on ft of class "B"
with 2% calcium chloride. Plug down at 7:	52 P M 12/26/82. Cemented second stag
	1. 1/4 ID. OI FIOCEIE DEI Sack, 12.53 IX
of gilsonite per sack, and 118 cu. ft. of c	class "B" with 2% calcium chloride.
Plug down at 11:57 P.M. 12/26/82.	
	•
	5
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is the and correct	
La The Kally Area Drod	Supt. DATE January 4, 1983
Dodd:	
(This space for Federal or State office use)	
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	ACCEPTED FOR RECORD
	MODEL LED LOU VEROUND

*See Instructions on Reverse Side

JAN 17 1983

