

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2050' FSL, 1135' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF-077085

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Omler A

9. WELL NO.
16

10. FIELD OR WILDCAT NAME
Harris Mesa Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 36, T28N, R10W

12. COUNTY OR PARISH
San Juan

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5894' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
3/4/83: MIRURT. Spud @ 3:00 pm, 3/4/83, w/4 Corners Rig #7. Drill 9-5/8" hole to 268'. Circ, POOH. Ran 7 jts 265' 7-5/8" 26.4# S-95 LT&C csg to 262'. Cmt w/118 CF Cl-B + 2% CaCl₂ + 1/4#/sx flocele. Displace plug to 231' w/wtr. Good circ. Cmt to surface. PD @ 7:00 pm, 3/4/83. WOC. NUBOP & test to 1000 psi, OK.
3/7/83: Drill to TD of 3155'. Circ, LDDP. Ran 101 jts 3139', 2-7/8" 6.5# J-55 EUE 8rd csg, set at 3151', float @ 3120'. Cmt w/925 CF HalcoLite + 1/4#/sx flocele, tail w/177 CF Cl-B + .2% CFR-2. Displace w/2% CaCl₂. PD @ 5:30 am, 3/8/83. Circ 20 bbls wash & 20 bble cmt. Rig released @ 6:00 am, 3/8/83.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ken Russell TITLE Sr. Production Analyst DATE March 9, 1983
Ken Russell

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

98