Form Approved. Budget Bureau No. 42-R1424

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	SF-080781	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME Cain	
1. oil gas 🔯 other	9. WELL NO.	
2. NAME OF OPERATOR	#24	
Southland Royalty Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Otero Chacra	
P.O. Drawer 570, Farmington, NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
below.)	Section 15, T28N, R10W	
AT SURFACE: 1520' FNL & 1010' FEL	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO.  15. ELEVATIONS (SHOW DF, KDB, AND WD)  5825' GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	- GOFF	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE	(NOTE: Report results and tiple completion of story change on Form 9–330.)	
CHANGE ZONES	TURKY / ON CON DI	
ABANDON*	WRIEY A SEST. 3	
(other) Spud & Casing Report X	1,000 s. 5 4 . 50	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface locations and	
5-17-83 Spudded 12-1/4" surface hole at 10 to a TD of 221'.	0:15 pm on 5-17-83 and drilled	

17	DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,
	including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and
	measured and true vertical denths for all markers and zones pertinent to this work )*

5-18-83 Set five joints (203') of 8-5/8", 24# casing at 215'. Cemented with 212 cubic feet of Class "B" containing 1/4# flocele and 3% CaCL2. Plug down at 8:30 am on 5-18-83. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Type		Set @ Ft.
18. I hereby certify that the foregoing is	true and correct	
SIGNED Shary Sterley	TITLE Secretary	DATE May 23, 1983
7	(This space for Federal or State office use)	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE

\*See Instructions on Reverse Side



20N 0 1 1983