UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Spud Casing Report

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

(other)

Dec. 1973	Budge	et Bureau No. 42-R1424
UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	SF - 079634	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT N	AME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas []	<u>McClanahan</u>	
well well tother	9. WELL NO.	
2. NAME OF OPERATOR	#22	
Southland Royalty Company	10. FIELD OR WILDCAT N	IAME
3. ADDRESS OF OPERATOR	Otero Chacra	
P.O. Drawer 570, Farmington, NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
below.) 3 10	Section 14, T2	8N. R1ŽW
AT SURFACE: 1620' FNL & 1620' FEL	12. COUNTY OR PARISH	
AT TOP PROD. INTERVAL:	San Juan	New Mexico
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
CONTRACT FOR APPROVAL TO CURRENT REPORT OF	5635' GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	en i juga mena seri in digi ka	
TEST WATER SHUT-OFF	/	

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" surface hole at 11:00 am on 5-22-83 and drilled to 5-22-83 a TD of 234'. Set five joints (217') of 8-5/8", 24#, casing at 229'. Cemented with 183 cubic feet of Class "B" containing 1/4#flocele and 3% CaCL2. Plug down at 630 pm on 11-22-83. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Type		Set @ Ft
18. I hereby certify that the	foregoing is true and correct	etary DATE <u>May 24, 1983</u>
SIGNED SIGNED	(This space for Feder	
APPROVED BY		DATE

*See Instructions on Reverse Side



JUN 11 : 1983