

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYIndian Agency DelawareStonerville

Allottee _____

Lease No. Stonerville Contract
No. 296

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|-----------------------------------------------------|-------------------------------------|--------------------------------------------------|
| NOTICE OF INTENTION TO DRILL _____ | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF _____ |
| NOTICE OF INTENTION TO CHANGE PLANS _____ | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____ |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____ | | SUBSEQUENT REPORT OF ALTERING CASING _____ |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____ | | SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____ |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____ | | SUBSEQUENT REPORT OF ABANDONMENT _____ |
| NOTICE OF INTENTION TO PULL OR ALTER CASING _____ | | SUPPLEMENTARY WELL HISTORY _____ |
| NOTICE OF INTENTION TO ABANDON WELL _____ | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 19, 1961

Well No. No. 1 is located 1800 ft. from S line and 1800 ft. from W line of sec. 13

| | | | |
|-------------------------------------------|----------------------------------------------|-------------------------------------------|-------------------------------|
| <u>Sec. 13</u> (1/4 Sec. and Sec. No.) | <u>20N</u> (Twp.) | <u>15</u> (Range) | <u>N.M.P.M.</u> (Meridian) |
| <u>Wildcat Dakota</u> (Field) | <u>Edo Arriba</u> (County or Subdivision) | <u>New Mexico</u> (State or Territory) | |

The elevation of the derrick floor above sea level is 7300 ft. (Indicated ground level.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Propose to: Set 180 feet of 9 5/8" surface casing and cement to surface. Drill with rotary to approximately 1800 feet or through Mesquite formation. Set 7" casing (intermediate) at 1800 ft. and cement with 30 cu. ft. Drill with air from 1800 to approximate total depth of 2000 ft. or through the Dakota formation. If none is productive, a 4 1/2" liner will be run and cemented. Produce and sand-water free. Run 2 1/8" tubing opposite pay zone.

N/4, Section 13, 60 acres, dedicated to well.

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Antec Oil and Gas CompanyAddress P. O. Drawer 570
Farmington, New Mexico

ORIGINAL SIGNED BY JOE C. SALMON

By Joe C. SalmonTitle District Superintendent