

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals.

FORM APPROVED

Budget Bureau No. 1004-0135

Expires March 31, 1993

5. Lease Designation and Serial No.
MDA 701-98-0013

6. If Indian, Allottee or Tribe Name
Jicarilla Apache Tribe

7. If Unit or C.A. Agreement Designation
N/A

8. Well Name and No.
Jicarilla 29-02-07 No. 2

9. Well API No.

30-039-26727

10. Field and Pool, or Exploratory Area
East Blanco; Pictured Cliffs

11. County or Parish, State
Rio Arriba County, NM

SUBMIT IN TRIPLICATE

MAY 2001

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other:

2. Name of Operator

Mallon Oil Company

3. Address and Telephone No.

P.O. Box 2797 Durango, CO 81302

(970 382-9100)

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2170' FSL and 2085' FEL, NW/SE, Unit J
Sec. 7, T29N, R02W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment ☐ Change of Plans
☐ Recompletion ☐ New Construction
☐ Plugging Back ☐ Non-Routine Fracturing
☐ Casing Repair ☐ Water Shut-Off
☐ Altering Casing ☐ Conversion to Injection
☒ Other: Plub and Abandon ☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)

Mallon Oil Company plugged and abandoned the above referenced well on April 14, 2001.

Plugs were placed as follows:

1st Plug - set from 2050'-2200', 9 bbls Slurry, Type III with 1% CaCl, 14.5 ppg.

2nd Plug - set from 950'-1100', 9 bbls Slurry, Type III with 1% CaCl, 14.5 ppg.

3rd Plug - set from 300'-200', 9 bbls Slurry, Type III with 1% CaCl, 14.5 ppg

Surface Plug - set from surface to 100', 6 bbls Slurry, Type III with 1% CaCl, 14.5 ppg

Last plug set at 1108 hours 04/14/01

Operations was witness by Al Yepa and Alfonso Atencio of the Bureau of Land Management.

14. I hereby certify that the foregoing is true and correct.

Signed

Gay Davis

Title Office Manager

Date 4/16/01

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved B

/s/ Brian W. Davis

Title

Lands and Mineral Resources

Date

MAY 2 2001

Conditions of approval, if any:

CONFIDENTIAL