(A	pril 19	831 b 852)	
	10		} 

(	pin i		
<u> </u>	¦	<del> </del>	
	19	<u> </u>	
	<b>)</b>		

SUBMIT	IN	TRIPLICATES

## **UNITED STATES** R

	ĺ	_		
DEPART	MENT	OF	THE	INTERIO
	GEOLOG	ICAL	. SUR	VEY

Indian Agency
Allottee

Budget Bureau No. 42-R359.4. Approval expires 12-31-80.

SUNDRY NOT		
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SE	HUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OF	SUBSEQUENT REPORT OF SHOOTING	OR ACIDIZING
NOTICE OF INTENTION TO REDRILL OR REPAIR	SUBSEQUENT REPORT OF ALTERING	CASING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.	SUBSEQUENT REPORT OF REDRILLI	NG OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASIN	SUBSEQUENT REPORT OF ABANDON	MENT
NOTICE OF INTENTION TO ABANDON WELL	G	
(INDICATE ABOVE BY	CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DA	
	OR OTHER DA	(TA)
Zall NI.	Hey 19	, 1940
ell No is located	o. ft. from S line and 1680 ft. from	line of sec. 19
(M Sec. and Sec. No.)	(Range)	
	(Meridian)	
(Field)	(County or Subdivision)	water
e elevation of there are floor above		State or Territory)
1100r above	ve sea level is 7108 ft.	
ite names of and sympatral days	DETAILS OF WORK	그 경기 나는 한번에는 나는
wapected depths to chiective can		and the second s
ing poin	ds; show sizes, weights, and lengths of proposed casings;	; indicate mudding inb.
ing poin	ds; show sizes, weights, and lengths of proposed casings ts, and all other important proposed work)	; indicate mudding jobs, coment-
ing point ing po	ds; show sizes, weights, and lengths of proposed casings ts, and all other important proposed work)	; indicate mudding jobs, coment-
ing point ing po	ds; show sizes, weights, and lengths of proposed casings ts, and all other important proposed work)	; indicate mudding jobs, coment-
ing poin ing po	ds; show sizes, weights, and lengths of proposed casings; ts, and all other important proposed work)  90', 96' - 3941' con w/190  100' by Reh-Row Roules Cooles	indicate mudding jobs, coment-
ing point ing po	ds; show sizes, weights, and lengths of proposed casings ts, and all other important proposed work)  13', 3' 3541' con w/130  130' by Resh-New Menico Cocing  130' squaesed w/40 Sn com,	indicate mudding jobs, coment-
ing poin ing poin 3541'. 10-3/4" surface pip 3541'. 10-3/4" surface pip 35'-3512', 3008'-3523'. Piu in for salvage. Perfecation source. Piug une set from 2 into cut off. Piug unt for	ds; show sizes, weights, and lengths of proposed casings; ts, and all other important proposed work)  10, 36, 364, 384, 488, 4/130  10, 36, 36, 384, 488, 488, 488, 488, 488, 488, 488	indicate mudding jobs, coment-
ing poin  1871lie - 5 No. 1  2541'. 10-3/4" eurface pip  8'-3512', 2008'-3523'. Plu  h for salvage. Perfecation  5eure. Plug use set from %  into cut off. Plug set from  6 et 118' and set plus from	ds; show sizes, weights, and lengths of proposed casings to, and all other important proposed work)  3341 cen w/130  3441 cen	sindicate mudding jobs, coment-
ing poin ing poin 1 3541'. 10-3/4" curface pip 3541'. 10-3/4" curface pip 8'-3512', 3608'-3523'. Plug in for salvage. Perfection 3: into cut off. Plug out fact at 118' and set plug from surface pipe and installed a	ds; show sizes, weights, and lengths of proposed casings to, and all other important proposed work)  10, 56, 3841, see w/190  100 by the flow flow feeting the see of the flow squares w/40 sx see, 1  100 to Th. Cut off see of the flow state of the see of the flow squares w/40 sx see, 1  1270 to 1477, Pulled Str.	sindicate mudding jobs, coment-
ing poin ing poin 3041'. 10-3/4" curface pip 3041'. 10-3/4" curface pip 8'-3012', 3008'-3023'. Plu h for salvage. Perfecation seure. Plug use set from X into cut off. Plug set for set 118' and set plug from surface pipe and installed x inspection.	ds; show sizes, weights, and lengths of proposed casings to, and all other important proposed work)  2	Findicate mudding jobs, coment-
3541'. 10-3/4' curface pip 6'-3512', 3608'-3523'. Plu h for salvage. Perfecation sture. Plug use set from X into cut off. Plug set for s et 118' and set plug from surface pipe and installed :	ds; show sizes, weights, and lengths of proposed casings; ts, and all other important proposed work)  1	ex. Perferations - Pallers of Vernal, ek gel w/400# - Pumped 20 ex seg. Placed bridge 10 can plus at top Piered. Bridge
3541'. 10-3/4' curface pip 6'-3512', 3608'-3523'. Plu h for salvage. Perfecation sture. Plug use set from X into cut off. Plug set for s et 118' and set plug from surface pipe and installed :	ds; show sizes, weights, and lengths of proposed casings; ts, and all other important proposed work)  2	ex. Perferations - Pallers of Vernal, ek gel w/400# - Pumped 20 ex seg. Placed bridge 10 can plus at top Piered. Bridge
3541'. 10-3/4" surface pip 8'-3512', 3608'-3523'. Plu h for salvage. Perfecation source. Plug use set from X into cut off. Plug set for s at 118' and set plug from surface pipe and installed :	ds; show sizes, weights, and lengths of proposed casings to, and all other important proposed work)  10	ex. Perforations . Pallers of Vernal, ek gel w/400# . Pumped 20 ex seg. Placed bridge 10 can plus at top rtored. Person
3541'. 10-3/4' curface pip 8'-3512', 3608'-3523'. Plu h for calvage. Perfecation sture. Plug use set from 2 into out off. Plug set fro into out off. Plug set from the at 118' and set plug from surface pipe and installed a inspection.	peed by the Her Memico Cooling was squares with the squares of the	Pallers of Vernal, at gol w/400%  Pumped 20 as reg. Placed bridge to can plug at top stored.
3541'. 10-3/4" surface pip 6'-3512', 3608'-3523'. Plu h for salvage. Perfecation sture. Plug use set from 2 into set off. Plug set fro into set off. Plug set fro at 118' and set plug from surface pipe and installed a inspection.	peed by the Her Memico Cooling was squares with the squares of the	Pallers of Vernal, at gol w/400%  Pumped 20 as reg. Placed bridge to can plug at top stored.
3541'. 10-3/4" surface pip 8'-3512', 3608'-3523'. Plu h for salvage. Perforation scure. Plug use set from X into cut off. Plug set fro into cut off. Plug set from the cut off. Plug set from the cut off. Plug set from the cut off. Plug set from the cut off. Plug se	peed by the Her Memico Cooling was squares with the squares of the	Pallers of Vernal, at gol w/400%  Pumped 20 as reg. Placed bridge to can plug at top stored.
3541'. 10-3/4" surface pip 8'-3512', 3608'-3523'. Plus h for salvage. Perfecation scure. Plus use set from X into cut off. Plus set from s at 118' and set plus from surface pipe and installed a inspection.	ds; show sizes, weights, and lengths of proposed casings; ts, and all other important proposed work)  1	Pallers of Vernal, at gol w/400% Pumped 20 as reg. Placed bridge to can plug at top stared.  RECEIVED  NAN 23 1960  Tations may be control of the control.
3541'. 10-3/4' surface pip 8'-3512'. 3808'-3523'. Plus h for salvage. Perfecation source. Plus use set from X into cut off. Plus set from 8 et 118' and set plus from surface pipe and installed a inspection.	peed by the Her Memico Cooling was squares with the squares of the	Pallers of Vernal, at gol w/400#  Pumped 20 as reg. Placed bridge to can plus at top stored.
3541'. 10-3/4" surface pip 8'-3512'. 3808'-3523'. Plus h for salvage. Perfecation source. Plus use set from X into cut off. Plus set from s et 118' and set plus from surface pipe and installed a inspection.	peed by Utah-New Menico Cooling were squaesed w/40 sx com, i no to Th. Cut off cos etazy no 1370 to 1477. Pulled the do to 110 w/20 sx com. Set cogulation marker. Location rec	Pallers of Vernal, at gol w/400% Pumped 20 as reg. Placed bridge to see plug at top started.  RECEIVED  NAV 23 1960 OIL DIST. 3
364' 10-3/4' curface pipes and sold and sold and sold plug sold from a late out off. Plug sold from a late out off. Plug sold from a late out off. Plug sold from sold and sold plug from surface pipe and installed a inspection.  Inspection.  Inspection.  Inspection.  Inspection.  Inspection.  Inspection.  Inspection.	per by the server series Casing was squared w/40 ex sem, i mo to Th. Cut off seg stary and 1370 to 1477'. Pulled by 60 to 110' w/20 ex sem. Set regulation marker. Location response in writing by the Geological Survey before oper ORIGINAL S	Pallers of Vernal, at gol w/400% Pumped 20 as leg. Placed bridge to can pluy at top stored.  RECEIVED  MAY 23 1960  OIL DIST. 3
2541'. 10-3/4" surface pip 8'-3512'. 2008'-2523'. Plus h for salvage. Perfecation scure. Plus use set from X into cut off. Plus set from s et 118' and set plus from surface pipe and installed a inspection.	peed by Utah-New Menico Cooling were squaesed w/40 sx com, i no to Th. Cut off cos etazy no 1370 to 1477. Pulled the do to 110 w/20 sx com. Set cogulation marker. Location rec	Pallers of Vernal, at gol w/400% Pumped 20 as leg. Placed bridge to can pluy at top started.  RECEIVED  MAY 23 1960  OIL DIST. 3
3641. 10-3/4" surface pip 8'-3512', 3608'-3523'. Plu h for salvage. Perforation sture. Plug use set from X into cut off. Plug set fro into cut off. Plug set fro tot 118' and set plug from surface pipe and installed a inspection.  apany Gulf Cil Corporation ress. Production Deportment Pa O. Ber 1346	pool by the more sense will be come agreement with the come agreement with the come at the come are come at the come	Pallers of Vernal, at gol w/400% Pumped 20 as leg. Placed bridge to can pluy at top stored.  RECEIVED  MAY 23 1960  OIL DIST. 3
Sidi. 10-3/4 curfose pip R'-3512', 2008'-3523'. Plu R'-3512', 2008'-352'. Plu R'-3512', 2008'-352	period by the decision with the second of th	Pallers of Vernal, at gol w/400% Pumped 20 as top. Placed bridge to can pluy at top stored.  RECEIVED  NAY 23 1960 Tations may be CONV. COM. OIL DIST. 3
3641'. 10-3/4" surface pip 8'-3512', 3608'-3523'. Plu h for salvage. Perfecation scure. Plug use set from X into cut off. Plug set fro into cut off. Plug se	period by the decision with the second of th	Pallers of Vernal, at gol w/400% Pumped 20 as leg. Placed bridge to can pluy at top started.  RECEIVED  MAY 23 1960  OIL DIST. 3

ARE ES YAM

TELE

TELE