


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **077975-1**
Lease No. **WELLS**
WELL 2 & SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHUT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 28th (thirtieth) 19 57

Well No. **2** is located **990** ft. from **N** line and **990** ft. from **W** line of sec. **33**
28 E **13 S** **106N**

(Twp) **28 E** (Range) **13 S** (Meridian) **106N**
(County or Subdivision) **San Juan County** (State or Territory) **New Mexico**

The elevation of the derrick floor above sea level is **5422.0** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands show sizes, weights, and lengths of proposed casings; indicate casing joints, cementing points, and all other important proposed work.)

3 shots at approximately 6400 T.D.

200' 2-1/2" surface casing - cemented top to bottom
2-3/4" hole to 25'.

Well: 5 as well location map

100' 2-1/2" surface casing - cemented top to bottom

2-3/4" hole to 25'.

3 shots at approximately 6400 T.D.

200' 2-1/2" surface casing - cemented top to bottom

2-3/4" hole to 25'.

3 shots at approximately 6400 T.D.

200' 2-1/2" surface casing - cemented top to bottom

2-3/4" hole to 25'.

3 shots at approximately 6400 T.D.

200' 2-1/2" surface casing - cemented top to bottom

2-3/4" hole to 25'.

3 shots at approximately 6400 T.D.

200' 2-1/2" surface casing - cemented top to bottom

2-3/4" hole to 25'.

Company

Address

By

Title



