

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SP 080844  
Unit Callegos Canyon Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Callegos Canyon Unit

Farmington, New Mexico July 27, 19 60

Well No. 88 is located 990 ft. from XX line and 1980 ft. from E line of sec. 31


SW/4 SE/4 of Section 31 T-28-N R-11-W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Undesignated Gallup San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6032 ft. (RDB)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 5925' - Plug back depth 5891'. Set 4-1/2" casing at 5925' with DV tool at 2081'. Cemented first stage with 100 sacks six percent gel cement with 1-1/2 pound tuf plug per sack followed by 100 sacks neat cement. Tested with 3000 psi for 30 minutes which held with no indication of pressure drop. Cemented second stage with 200 sacks six percent gel cement with 1-1/2 pound tuf plug per sack. Tested DV tool with 2500 psi for 30 minutes which held with no indication of pressure drop. Received good circulation throughout on both stages. Drilled DV tool at 2081' and cleaned out to plug back depth. Tested 4-1/2" casing with 1000 psi which held with no indication of pressure drop. Released rig July 26, 1960.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Fan American Petroleum Corporation

Address P. O. Box 460

Farmington, New Mexico

Attn: L. C. Speer, Jr.

ORIGINAL SIGNED BY  
R. M. Bauer, Jr.

By \_\_\_\_\_

Title Area Engineer