

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan
Initial X Annual _____ Special _____ Date of Test 7-13-64
Company PAN AMERICAN PETROLEUM CORP. Lease Gallegos Canyon Unit-Dak Well No. 146
Unit X Sec. 34 Twp. 38N Rge. 12W Purchaser El Paso Natural Gas Company
Casing 4-1/2 Wt. 10.5 I.D. 4.052 Set at 6284 Perf. 6101-15 To 6043-60
Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 6035 Perf. 6034 To 6018
Gas Pay: From 6043 To 6152 L 6100 xG .700 -GL 4270 Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well Single
Date of Completion: 7-8-64 Packer None Reservoir Temp. _____
Single-Bradenhead-G. G. or G.O. Dual

OBSERVED DATA

Tested Through (Packer) (Choke) (Manometer) Type Taps Flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(<u>Pressure</u>) (Line) Size	(<u>Choke</u>) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI	<u>7 Days</u>					<u>2034</u>		<u>2034</u>		
1.	<u>2 Inch</u>	<u>.750</u>	<u>332</u>			<u>332</u>	<u>60° est.</u>	<u>1109</u>	<u>60° est.</u>	<u>3 Hr.</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.3630</u>		<u>544</u>	<u>1.0000</u>	<u>.9238</u>	<u>1.073</u>	<u>6663</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS


Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2072 P_c 4,293,164

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						<u>1,394,761</u>	<u>2,093,423</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 8973 MCFPD; n .73
COMPANY PAN AMERICAN PETROLEUM CORPORATION
ADDRESS BOX 400, ALBUQUERQUE, NEW MEXICO
AGENT and TITLE V. L. Moore, District Engineer
WITNESSED By: ORIGINAL SIGNED BY
COMPANY E. W. Felt

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .