Form 3160-5 UNITED STAT November 1983) Formerly 9-331)  BUREAU OF LAND MAN	INTERIOR Terre	IT IN TRIPLICATES Instructions on re- side)	Form approved.  Budget Bureau No. 1004-0135 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO.  SF-077978-C
SUNDRY NOTICES AND RE  (Do not use this form for proposals to drill or to deep  use "APPLICATION FOR PERMIT—	PORTS ON WEL en or plug back to a diff of for such proposals.)	LS erent reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAR OTHER			7. UNIT AGREEMENT NAME  8. PARM OR LEASE NAME
DUGAN PRODUCTION CORP.			Fullerton
ADDRESS OF OPERATOR		•	9. WELL NO.
P O Box 208, Farmington, NM 87499  LOCATION OF WELL (Report location clearly and in accordance also space 17 below.)  At surface	ce with any State require	EIVED	10. FIELD AND POOL OF WILDCAT Amarillo-Gallup/ Basin Dakota
1850' FNL & 1850' FWL	n L O		11. SNC., T., R., M., OR BLK. AND SURVEY OR ARMA
		v 2 <b>0</b> 1985	Sec.34,T28N,R13W, NMPM
14. PERMIT NO. 15. BLEVATIONS (Sh		LAND MANAGEMENT	San Juan NM
6. Check Appropriate Box To		Intice Report, or C	
notice of intention to:			THIT REPORT OF:
FRACTURE TREAT SHOOT OR ACIDIZE  TEST WATER SHUT-OFF PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON®	FRAC	TUBE TREATMENT OTING OR ACIDIZING	ERPAIRING WELL XX  ALTERING CASING  ABANDONMENT®
REPAIR WELL CHANGE PLANS	(Oth	(None - Pancet results	of multiple completion on Well
(Other)  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state)  18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state)	all pertinent details, an	1 -l nMasst dates	etion Report and Log form.) including estimated date of starting any it denths for all markers and zones perti-
proposed work. If well is directionally drilled, give an nent to this work.) *		astired and true retries	
Remedial Work 11-8-85 thru			
M.I. & R.U. Pulling Unit. packer and located hole in Iron Bridge Plug @ 4990' or sx class "B" cement. Drill 1050 psi. Held OK. Drille "D" packer @ 6170' and cleat tubing @ 6210' with 5½" Bak side with inhibited packer	casing between wireline. Squed out cement a dout bridge pland out to 6256 er Model "R" pa	3363' and 3394 Deezed hole in Ond pressure te Ond 0 4990'. Mi	casing with 150 cast casing with 150 casing to 11ed out model anded 2-3/8"
•			
			REGERVED
			NOV 2 2 1985
		- ·	
•		-	383
		· · · · · · · · · · · · · · · · · · ·	
	Geolog	jist -	11-19-85
(This space for Federal de State office use)	nitle		NOV-20 1985
APPROVED BY			FARMINGTON RESOURCE AREA

\*See Instructions on Reverse Side

SAW SWW