

(SUBMIT IN TRIPLICATE)

Indian Agency

College Campus Unit

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee

Lease No. **I-349-IND-8477**

X		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	2-3/8"	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING		
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT		
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	Cero	X
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Gallegos Canyon Unit

Farmington, New Mexico August 9, 1963

Well No. 140 is located 1915 ft. from S line and 2070 ft. from W line of sec. 29

NE/4, SW/4 Section 29
(1/4 Sec. and Sec. No.)

7-2021

(Twp.)

R-12W

(Range)

N.M.P.M.
(Meridian)

Cha Cha Calling
(Field)

~~San Juan~~
(County or Subdivision)

New Machine
(State or Territory)

RECEIVED

1963

The elevation of the derrick floor above sea level is _____ ft. **(To be reported later.)**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The above well was spudded on August 2, 1963 and drilled to a total depth of 229'. 8-5/8" casing was set at that depth with 235 sacks cement containing 2% calcium chloride. Cement circulated to surface. After waiting on cement tested casing with 500 psi for 30 minutes. Test ok. Reduced hole to 7-7/8" and resumed drilling.

Core No. 1 - 5201-5252 (Gallup) Cut 51', recovered 51' as follows: 5201-06 sand good porosity and stain; 5206-08 sand tight and shaley; 5208-5252 shale, sandy black. Drilled to a total depth of 5205 and 4-1/2" casing was set at that depth. Stage tool set at 1456. Cemented first stage with 125 sacks Quixtongh cement containing 45 Gal, 1-1/2 pounds medium Tuf Plug per sack followed by 75 sacks Quixtongh next. Second

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address P. O. Box 180

Farmington, New Mexico

Attest: _____

By

Title Petroleum Engineer

ORIGINAL SIGNED BY
F. H. HOLLINGSWORTH

AUG 14 1963

OIL CON. COM.
DIST. 3

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010

10/10/2010