



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 078904

Unit Gallegos Canyon Unit

RECEIVED

ORIGINAL SUP
NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Gallegos Canyon Unit

Farmington, New Mexico December 29, 1958

Well No. 83 is located 990 ft. from [N] line and 990 ft. from [E] line of sec. 26

NE 1/4 of Section 26
(1/4 Sec. and Sec. No.)

T-28-N
(Twp.)

R-12-W
(Range)

NMPM
(Meridian)

Wildcat
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 5617 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Gallegos Canyon Unit Well No. 83 - On December 13, 1958, 7" casing was landed at 6343' with Baker DV Tool at 1283'. Cemented first stage with 300 sacks 6 per cent gel cement with 2 pound medium buff plug per sack, followed by 75 sacks neat cement. Lost approximately one-half returns during displacement on last 25 barrels. Bumped plug and tested casing with 2000 pounds pressure for thirty minutes, which held with no drop in pressure. After waiting on cement for six hours, cement second stage with 200 sacks 4 per cent gel cement with full returns through second stage. Tested casing with 2000 pounds which held OK. Drilled out stage collar and drilled cement to 6325'.

Released Rotary Rig December 15, 1958.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 467

Farmington, New Mexico

ORIGINAL SIGNED BY
D. J. SCOTT

By

Title Field Clerk