

SUMMARY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PURPOSES TO DEPEND ON TO OBTAIN OR LOST DATE OF A LICENSE OR PERMIT.
US APPLICATION FOR PERMIT - FOR SUCH DEVELOPMENT

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

Southland Royalty Company

ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, New Mexico 87499

LOCATION OF WELL Report location clearly and in accordance with any State requirements.*
See also space 17 below.
At surface

660' FNL & 1960' FWL

Navajo Tribe

UNIT AGREEMENT NAME

Gallegos Canyon unit

FARM OR LEASE NAME

~~Gallegos Canyon unit~~

WELL NO.

129

10. FIELD AND POOL, OR WILDCAT

Cha Cha Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Seciton 30, T28N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

PCILL OR ALTER CASING ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☒

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

SRC has tested this well since September, 1983. Production is uneconomic; therefore, SRC proposes to abandon this well as previously authorized (copy attached).

RECEIVED
MAY 11 1984
OIL CON. DEPT.
DIST. 3

I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE Petroleum Engineer

DATE 5-2-84

This space for Federal or State office use

APPROVED

APPROVED BY

TITLE

DATE 5-2-84

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

[Signature]
M. MILLENBACH
AREA MANAGER

*See Instructions on Reverse Side

18 USC 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

AMOCO PRODUCTION COMPANY
OIL & GAS

10. FIELD AND TOOL, OR WILDCAT
Cha Cha Gallup

11. SEC. T. R. M. OR BLM. AND
SURVEY OR AREA
Sec. 30-T28N-R12W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, AT, OR, CUL.)
5758' KB

660' ML, 1960' WL, Section 30-28N-12W
Unit Letter C

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	FRACTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other)	☐
(Other)	☐	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
PULL OR ALTER CASING	☐	REPAIRING WELL	☐
MULTIPLE COMPLETE	☐	ALTERING CASING	☐
ABANDON*	☒	ABANDONMENT*	☐
CHANGE PLANS	☐		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and pertinent to this work.)

Status: 8-5/8" surface pipe at 200'. Base Ojo Alamo estimated 203'. DV tool 1715'. Perforations 5453-57'. 4-1/2" casing in 7-7/8" hole. Depleted oil well.

Propose to plug well as follows:

1. Fill hole with gel-mud. Place 10 sxs. cement (130') plug from 5457-5327'.
2. Place 10 sxs. cement (130') plug from 1780' to 1650'.
3. Cut 4-1/2" casing at free point (top of annular cement calculated 477') and pull same. Fill hole with gel-mud. Place 30 sxs. cement (160') plug bottomed 75' below casing cut.
4. Place 30 sxs. cement (100') plug from 250' to 150'.
5. Place 30 sxs. cement (37') plug in top of surface pipe.
6. Cut off pipe at bottom of cellar, place one sack cement on top of pipe and install regulation marker.
7. Clean up and level location to as near original contour as practicable.

AMOCO PRODUCTION COMPANY

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
MAY 11 1964
OIL CON. B.V.
DIST.