Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Cline Size Size psig hw OF. psig OF. ps	Pool	-11est	يعيو ديوانڪ بيدرجيوا، ڪا 7 شون		ŕ'(rmation	1	Dakota		County	Se	a Juan
Sec. 12	Initi	al <u>*</u>		Annua	1		Spec	cial		Date of	Test	7-14-59
### A Property of the property	ompa:	ny Rod	ern er	rd He	TR.		Lease	Ph111	<u>lps</u>	Wel	Ll No	
### Property Continue Press Pres	nit	_ ? S	Sec	Twp		esu Rg	e. 11¥	Purc	haser			
Refaired Packer Type Well Single-Bradenhead-G. G. or G.O. Dual	asin	g	it. 15.	5 €1.	D	Se	t at	6234 Pe	rf. 6	203	_To	60 71
Tubing	ubin	g 3 3/8"	it. 🍇	7 I.	D	Se	t at	6141 Pe	rf	242	То	6138
The control of the co	as Pa	ay: From_	6031	To	6803	L	χχ	G •.64	-GL_		Bar.Pr	ess
The control of the co	rodu	cing Thru:	Casi	ng		Tu	bing	X	Type We	ell S	nglo	ÇAS
OBSERVED DATA Sted Through (From (Choke) (Miles) Flow Data Flow Data Flow Data Flow Data Flow Chine (Orifice) (Orifice) Size Size psig hw of press. Temp. Press. Temp. Of Flow of Flow Size Size psig hw of psig hw of psig of the first state of the first st								Sin	gle-Brade	enhead-G.	G. or	G.O. Dual
Flow Data Tubing Data Casing Data Casing Data Choke Choke Press Diff Temp. Press Temp. Press Temp. Of Flow Size Press Diff Temp. Press Temp. Press Temp. Of Flow Size Press Temp. Of Flow												i
Flow Data Tubing Data Casing Data Casing Data Choke Choke Press Diff Temp. Press Temp. Press Temp. Of Flow Size Press Diff Temp. Press Temp. Press Temp. Of Flow Size Press Temp. Of Flow	estec	i Through	(P	₩ (0)	hoke)	(56646)	j.			Type Tap)S	
C(Prover) (Choke)								Tubing	Data			1
FLOW CALCULATIONS Coefficient (24-Hour) Pressure Pressure Flow Temp. Factor Facto	0.		(Chok	e) [Diff.	Temp.				+	
FLOW CALCULATIONS Coefficient	İ	, ,	1 '		psig	h _w	°F.	psig	°F.	psig	°F∙	i
FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow Factor Factor	I							2026		2307	 	
FLOW CALCULATIONS Coefficient			3/1	*	671		72			1891		3 hps.
FLOW CALCULATIONS Coefficient												
Coefficient (24-Hour) Pressure Flow Temp. Factor			L				ETOW CAI	CIII A TTOM	<u> </u>			
PRESSURE CALCULATIONS Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Specific Gravity Flowing Fluid Pc 11.05c Pc 11.05	T	Coeffici	ent		Pr		Flow	Temp.	Gravity	Compre	ss.	
PRESSURE CALCULATIONS Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Specific Gravity Flowing Fluid Pc		(24-Hou	r) 7	hwpj	e	psia					- 1	@ 15.025 psia
PRESSURE CALCULATIONS Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Specific Gravity Flowing Fluid Pc												
PRESSURE CALCULATIONS Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Specific Gravity Flowing Fluid Pc		12, 3650				683	, 988	7	. 2222	1,08	9	6429
Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Specific Gravity Flowing Fluid Pc	土											
vity of Liquid Hydrocarbons deg. Pw Pt						PRI	ESSURE C	ALCUL ATI	ONS			
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$									-			
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	-	_	-	(1-	-e ^{-s})		ueg•		Pc-	110 Gravi	_Pc	4490
Pt (psia)		· · · · · · · · · · · · · · · · · · ·				 				ı 		· · · · · · · · · · · · · · · · · · ·
solute Potential: MCFPD; n MCF) • l		$P_{\mathbf{t}}^2$	Fc	2	$(F_cQ)^2$	(F	_c Q) ²	P_w^2	$P_c^2 - P_w^2$		
solute Potential: MCFPD; n MCF		't (psia)						-€~5)			- I	W Pc
solute Potential: MCFPD; n 7 1.655 MPANY DRESS ENT and TITLE TINESSED MPANY		487							2199	2291		1.90
MCFPD; n MCF											1	
DRESS ENT and TITLE UNESSED MPANY	osolu	te Potent	ial:	3,95	0		MCFPD;	n .75	1,655			
MPANY	DRES	SS	1707	**	dit and	-						
MPANY			T.R.				STATE N	MET NO ST				
OFI.HVFN							MTR	ARKS		AFI		
							TUM	. 4.1.41.2.1.2		OFI'H	VFN	\

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- PcI 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw= Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

of the second second	- OMINIS	SSIUN							
AZTEC DISTRICT OFFICE									
No. Copies Received 3									
DISTRIBUTION									
	NO. FUM: ISHED								
Convertor									
Santa Fe									
Projection Ortus	and the second s								
ete Land Office	and the second s								
U. S. G. S.		_							
Transporter		-							
File		1							