



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078904
Unit Gallegos Canyon Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Sand Frac</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico May 2, 1956

Well No. 76 is located 990 ft. from DD line and 1450 ft. from EW line of sec. 23

SW/4 of Section 23 T-28-N R-12-W NMSPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
West Kuts-Pictured Cliffs San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5736 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On April 17, 1956, this well was perforated with four jet shots per foot from 1545 feet to 1560 feet.

This well was then sand-water fraced with 27,000 gallons water and 30,000 pounds sand. Formation broke at 2250 pounds, treating pressure was 1700 pounds. Average injection rate was 48 barrels per minute. Preliminary test after frac was 750 MCFFD.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company AMERICAN OIL & GAS COMPANY

Address 1000 N. 1st St. Farmington, N.M.

By [Signature]

Title Field Superintendent

