COPY FOR STATE OF NEW MEXICO OIL CONSERVATION **COMMISSION** SUBMIT IN TRIPLICATE TO DISTRICT OFFICE

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office Santa Po
Lease No. 078807
Unit_I-Sec. 844
(Gallegos Canyon Unit)

	1	SURSEQUENT DES	PORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE	F PI ANS		PORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST W	ī	·	PORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRI	i		PORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT	l l	ii ii	PORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL O		11	WELL HISTORY
NOTICE OF INTENTION TO ABANDO	1	11	
CINDICATE	ABOVE BY CHECK MARK N		NOTICE, OR OTHER DATA)
Vell No. 5 is		•	990 ft. from E line of sec
Wildcat (Field)	San Juan (County	or Subdivision)	New Mexico (State or Territory)
	DETAI	LS OF WORK	
State names of and expecte indicate mudd	d depths to objective sa lling jobs, cementing po	nds; show sizes, vints, and all other	weights, and lengths of proposed casi important proposed work)
State names of and expecte indicate mudd	lling jobs, cementing po	nds; show sizes, vints, and all other	weights, and lengths of proposed casi important proposed work)
indicate muddell spudded Sept. 25 n Sept. 26, 10-3/limitroulated to surface	iling jobs, cementing po 5, 1951 casing landed at - set 2h hours. plug, tested cas	100° with 90	weights, and lengths of proposed casi important proposed work)  sacks cement, cement  shut off with 600 lb.
indicate muddell spudded Sept. 25 in Sept. 26, 10-3/limite irculated to surface in Sept. 27, drilled ressure 30 minutes - rilling resumed.	S, 1951  casing landed at a set 24 hours. plug, tested cas No drop in pres	100' with 90 ing and water	important proposed work)  sacks cerent, cement
indicate mudded sept. 25 in Sept. 26, 10-3/h irculated to surface in Sept. 27, drilled ressure 30 minutes rilling resumed.	casing landed at - set 2h hours. plug, tested cas No drop in pres	100° with 90° ing and water sure.	important proposed work)  sacks cement, cement  shut off with 600 lb.
indicate mudded sept. 25  In Sept. 26, 10-3/h  irculated to surface in Sept. 27, drilled ressure 30 minutes rilling resumed.  I understand that this p operations may be com	casing landed at - set 2h hours. plug, tested cas No drop in pres	100° with 90° ing and water sure.	important proposed work)  sacks cement, cement  shut off with 600 lb.