(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Santa Pe	
Lease No. 5F-678607-A	
Unit Callegos Canyon	Unit

SUNDRY N	OTICLS AND KEI OKTS OF WELLS
	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO DRILL	
OTICE OF INTENTION TO CHANGE PLAN	
OTICE OF INTENTION TO TEST WATER S	
OTICE OF INTENTION TO RE-DRILL OR	
IOTICE OF INTENTION TO SHOOT OR AC	
NOTICE OF INTENTION TO PULL OR ALTI	
IOTICE OF INTENTION TO ABANDON WEL	
(INDICATE	ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Hallegos Canyon Unit	Farmington, New Mexico July 21 , 19
all No. 100 is located	476 ft. from \mathbb{R}^{N} line and \mathbb{R}^{20} ft. from \mathbb{R}^{U} line of sec. \mathbb{R}^{20}
E/4 SW/4 of Section 12 (1/2 Sec. and Sec. No.)	2 T-28-N R-13-W N.B.FR. (Twp.) (Range) (Meridian)
	San Juan Rew Metal.
otah Gallup	(County or Subdivision) (State or Territory)
tate names of and expected depths to ob	DETAILS OF WORK Dispective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come ing points, and all other important proposed work) 17 18, 1961. Set 8-5/88 Gasing et 2138 with 175 secks
tate names of and expected depths to ob 3midded 12-1/4" hole Journaling 2	DETAILS OF WORK Directive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) Ly 18, 1961. Set 8-5/8* casing at 213* with 175 sacks percent Calcium Chloride. Circulated 25 sacks comentumes, tested 8-5/8* casing with 500 psi for 15 minutes, leation of pressure drop. Reduced hole to 7-7/8* at 2.
andded 12-1/4" hole of all coment containing 2 waited on cement 12 ho which held with no ind Reviewed drilling operations of the content of t	DETAILS OF WORK Discrive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) Aly 18, 1961. Set 8-5/8* casing at 213* with 175 socks percent Calcium Chloride. Circulated 25 sacks committees, tested 3-5/8* casing with 500 pai for 15 minutes, 10 testion of pressure drep. Reduced hole to 7-7/8* at 2: tions. A Petroleum Corporation ORIGINAL SIGNED BY
Junderstand that this plan of work not company Pen American delications	DETAILS OF WORK Discrive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come ing points, and all other important proposed work) 11 18, 1961. Set 8-5/8n casing at 213 with 175 socks percent Calcium Chloride. Circulated 25 sacks coment. 12 18, 1961. Set 8-5/8n casing at 500 psi for 15 minutes, urrs, tested 8-5/8n casing with 500 psi for 15 minutes, ication of pressure drop. Reduced hole to 7-7/8n at 2: 13 1961 11 25 1961 11 25 1961 11 25 1961 ORIGINAL SIGNED BY R. M. Bauer, Jr.