

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078905

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Gallegos Canyon Unit-GPA "D"

8. FARM OR LEASE NAME

9. WELL NO.

259

10. FIELD AND POOL, OR WILDCAT

Pinon Gallup11. SEC., T., R., M., OR BLOCK AND SURVEY
OF AREA**SE 1/4 SE 1/4 Section 14,
T-28-N, R-12-W**

12. COUNTY OR

San Juan

13. STATE

New Mexico

1a. TYPE OF WELL:

OIL
WELL ☐GAS
WELL ☐DRY ☐

Other

Injection

b. TYPE OF COMPLETION:

NEW
WELL ☒WORK
OVER ☐DEEP-
EN ☐PLUG
BACK ☐DIFF.
RESVR. ☐

Other

2. NAME OF OPERATOR

FAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 480, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

740' PSL & 810' FEL

At top prod. interval reported below

At total depth

Same

14. PERMIT NO.

DATE ISSUED

MAR 16 1967**U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.**

15. DATE SPUDDED

2-13-67

16. DATE T.D. REACHED

2-19-67

17. DATE COMPL. (Ready to prod.)

3-7-67

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

RKB 5790'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

5830'

21. PLUG, BACK T.D., MD & TVD

5795'22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY**Surf. to 5830'**

ROTARY TOOLS

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

5722-5736' Pinon Gallup25. WAS DIRECTIONAL
SURVEY MADE**No**

26. TYPE ELECTRIC AND OTHER LOGS RUN

Induction Electric

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	258'	12-1/4"	150 sacks	None
4-1/2"	10.5#	5830'	7-7/8"	1650 sacks	None

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	5695'	5694'

31. PERFORATION RECORD (Interval, size and number)

5722-5736' 4 shots per foot

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5722-5736'	300 gallons 7-1/2% acid

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
		Water Injection Well					Shut In	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
			→					
FLOW. PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
		→						
34. DISPOSITION OF PRODUCTION (If sold, use for fuel, vented, etc.)						TEST WITNESSED BY		

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

G. W. Eaton, Jr.

TITLE

Area Engineer

DATE

March 15, 1967

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22 and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:			38. GEOLOGIC MARKERS	
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				
FORMATION	TOP	BOTTOM	NAME	MEAS. DEPTH
				TRUE VERT. DEPTH
Surface and 4 shale	0	1665'		
Pictured Cliffs	1665'	1820'		
Lewis Shale	1820'	3205'		
Messverde	3205'	4410'		
Mancos	4410'	5307'		
Gallup	5307'	5723'		
Pineau Gallup	5723'	5830'		