

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP-078780

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Callegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.

266

10. FIELD AND POOL, OR WILDCAT

Undesignated Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

**SE/4 SE/4 Section 18,
T-28-N, R-11-W**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1130' FSL & 1000' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

CL 5549', RDB 5560'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☒

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Spud & set casing ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Callegos Canyon Unit No. 266 was spudded August 15, 1971 with a 12-1/4" hole. The 8-5/8" casing was set at 580' with 400 sacks Class "C" cement with 2% CaCl. The cement did not circulate and pumped 130 sacks down the casing backside. Circulated out cement. Reduced hole to 7-7/8" at 580' and drilled to TD 3230'.

The 4-1/2" casing was set at 3222'. Cemented the first stage with 450 sacks Type "C" with 6% Gel, 50-50 Pozmix and 2 pounds medium Tuf Plug per sack followed with 100 sacks Class "C" Neat. Cemented second stage with 265 sacks cement followed by 50 sacks neat. Cement circulated on both stages.

Cleaned out well to PBD 3183'. Set Abrasijet at 3144' and perforated 2 holes at 3144'. Pumped 2 barrels water at 2000 pounds. Loaded hole with water. Ran gauge ring and junk basket. Perforated 3130-33, 3086-92, 3080-82, 3042-44, 3034-37 x 2 SPV. Swab tested tubing 3-1/2 hours and recovered 45 barrels lead water and 101 barrels new water and slight trace gas each swab run. Shut in well and then swab tested 277 barrels salty formation water. Well is presently shut in.

18. I hereby certify that the foregoing is true and correct

SIGNED

D.A. Wadsworth

TITLE

Area Engineer

CON. COM.

DATE

September 9, 1971

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.