16.

UNITED STATES SUBMIT IN TRIPLICATE* Other instructions on reverse side)

Form approved. Budget Bureau No. 42-B1424,

5. LEASE DESIGNATION AND SERIAL NO.

SF-078863 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

GEOLOGICAL SURVEY								
SUNDRY	NOTICES	AND	REPORTS	ON	WELLS			

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			
OIL GAS X OTHER	7. UNIT AGREEMENT NAM	d E	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME		
R & G Drilling Company	Krause		
3. ADDRESS OF OPERATOR	9. WELL NO.		
c/o Walsh Engr. & Prod. Corp. P.O.Box 254, Farmington,			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* N.M. See also space 17 below.) At surface	10. FIELD AND POOL, OR Kutz Fruit		
1850'FSL, 1755'FWL	11. SEC., T., R., M., OR BI SURVEY OR ARBA Sec. 28-T2 N.M.P.M.		
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE	
5794'GL, 5804'DF, 5805'KB	San Juan	N.M.	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT®
REPAIR WELL		CHANGE PLANS		(Other) (Note: Report results of mu Completion or Recompletion F	ltiple completion on Well teport and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spud well. 9/7/78

9/7/78 T.D. 127'

Ran 2 jts., 8-5/8", 24.0 lb., K-55 casing (83.20') set at 95.20', with 100 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.

9/10/78 T.D. 1751'

> Ran 50 jts., 45", 10.50 lbs., K-55 casing (1739.78). at 1748.28' with 500 gallons Mud Flush followed by 150 sacks 65/35 Pozmix (12% gel) followed by 260 sacks 50/50 Pozmix with 64 lbs. Gilsonite per sack.

FOR: R & G Drilling Company 18. I hereby certify that the foregoing is true and corpect President, Walsh Engineering 9/26/78 TITLE & Prod. Corp. Ewell N (This space for Federal or State office use) DATE APPROVED BY CONDITIONS OF APPROVAL, IF ANY: