

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deeper or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR  
P O. Box 3280, Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1520' FSL, 1530' FEL (NW/SE)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐


## SUBSEQUENT REPORT OF:

|                                     |   |
|-------------------------------------|---|
| <input checked="" type="checkbox"/> | RECEIVED  |
| <input type="checkbox"/>            | JAN 18 1980   |
| <input type="checkbox"/>            | (NOTE: Report results of multiple completion or zone change on Form 9-330.) |
| <input type="checkbox"/>            | U. S. GEOLOGICAL SURVEY   |
| <input type="checkbox"/>            | FARMINGTON, N. M.   |

5. LEASE  
SF-078106
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Gallegos Canyon Unit
8. FARM OR LEASE NAME  
Gallegos Canyon Unit
9. WELL NO.  
290
10. FIELD OR WILDCAT NAME  
Kutz Pictured Cliffs, West
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 15-T28N-R12W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
GRD 5,660' KB 5,670'

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pictured Cliffs sand perfed 1,496'-1,500'; 1,512'-19' w/1 JSPF.  
Broke down perfs w/750 gals 15% HCl + additives. Fraced perfs  
w/24,000 gals 70% Quality Foam + 40,000# 10-20 sand @ 2 PPG.



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Alan B. Barnes TITLE Dist. Prod. Engr- RMD DATE 1-14-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOC

\*See Instructions on Reverse Side