
4

UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE 5. SF-078106 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME Gallegos Canyon Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	9. WELL NO. 1444 1 2 22 2
2. NAME OF OPERATOR Energy Reserves Group, Inc.	315 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	West Kutz Pictured Cliffs
P.O. Box 3280 - Casper, Wyoming 82602	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA এইডিল টু লুট্য Sec. 21-T28N-R12W এইডিজ
AT SURFACE: 1,685' FNL & 1,540' FWL (SE/NW)	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 ELEVATIONS CHOW DE VOE
The second secon	15. ELEVATIONS (SHOW DF, KDB, AND WD) G.L. 5,522 - K.B. 5,524
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	17/1661
SHOOT OR ACIDIZE	
REPAIR WELL	(NOME: Report results of multiple completion or zone change on Form 9-330)
MULTIPLE COMPLETE	Section 2 section 1
CHANGE ZONES	
ABANDON* (other) Well History X	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent lates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
The above referenced well was spudded @ 10:30	生活 속을 가는 것 같다.
Drilled 9-7/8" hole to 130' and set 7" 0.D., 1	17#. K-55. R-3 new casing Set 0
122' w/65 sx of Class "B" cement w/2% CaCl ₂ ar @ 4:45 PM 2-28-81.	nd /14# Flocele/sx. Plug down
Nippied up and pressure tested BOPE to 500 psi	ineid ok. aggree
Drilled 6-1/4" hole to 1,535' and ran logs to	
Ran 4-1/2" O.D., 10.5#, K-55, R-3, ST&C new ca	sing set $0.1.525$. Cemented $w/200$
sx of 50-50 Pozmix w/2% Gel; 0.5% D-31 & 1/4#	Celloflake/sx. Plug down @ 9:10 PM
3-2-81. Good cement returns.	### #################################
	1) 10 mm m m m m m m m m m m m m m m m m m
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	1.00 mg
SIGNED Karcoc C, Gillegietitle Drlg Supt - R	MD DATE 3-3-81
(This space for Federal or State offic	ce use)
APPROVED BY TITLE	ALLEPIEU FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:	SALE CAPE CAPE
	2-MADE 1-32 100 \$ 20 1
	2 S O M 4 8 7 M
*See Instructions on Reverse Si	de 등 기계

*See Instructions on Reverse Side