

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 3280 - Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1,850' FSL & 820' FEL (NE/SE)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☐

(other) Well History

## SUBSEQUENT REPORT OF:

- ☒
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☒

5. LEASE  
I-149-Ind-8470
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Allotted
7. UNIT AGREEMENT NAME  
Gallegos Canyon Unit
8. FARM OR LEASE NAME
9. WELL NO.  
320
10. FIELD OR WILDCAT NAME  
West Kutz Pictured Cliffs
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 30-T28N-R12W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
G.L. 5,631'; K.B. 5,633'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above referenced well was spudded @ 9:00 AM 4-4-81.

Drilled 9-7/8" hole to 125'. Ran 3 jts 7" O.D., 17#, H-40 new casing set @ 125'. Cemented w/65 sx of Class "B" cement w/2% CaCl<sub>2</sub> & 1/4# Celloflake/sx. Plug down @ 2:30 PM 4-4-81/ Good cement returns.

N.U. &amp; tested BOPE to 500 psi--held o.k.

Drilled 6-1/4" hole to 1,450' and ran logs.

Ran 36 jts 4-1/2" O.D., 10.5#, K-55, R-3, ST&C new casing @ 1,420'. Cemented w/200 sx of 50-50 Pozmix w/2% Gel & 1/4# Celloflake/sx & plug down @ 12:15 AM 4-7-81. Good circulation throughout--but no cement. Ran temp survey--top of cement @ 400'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R.C. Villagran TITLE Drlg. Supt - RMD DATE \_\_\_\_\_

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

NMOCC