Form Approved. Budget Bureau No. 42-R1424

DEPARTMENT OF THE INTERIOR	5. LEASE NM-03179
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Aztec
	9. WELL NO. #10
NAME OF OPERATOR Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Kutz Fruitland
P.O. Drawer 570, Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 1040' FNL & 865' FEL	Section 14, T28N, R11W
AT TOP PROD. INTERVAL:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AFI NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	5760' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3700 dL
TEST WATER SHUT-OFF	$x^{\mu} \in A_{\mu} \times A_{\mu}$
FRACTURE TREAT	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	the spine of the
CHANGE ZONES	· · · · · · · · · · · · · · · · · · ·
(other) Casing Report X	and the state of the control of the
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 9-11-83 Pressure tested casing to 600 psi. 9-13-83 Drilled 6-3/4" hole to a total depth of 2-7/8", 6.4#, J55 casing set at 1685'. C feet of Class "B" containing 50/50 POZ, 6% g 70 cubic feet of Class "B" containing 2% CaC Top of cement at 500' by temperature survey.	irectionally drilled, give subsurface locations and to this work.)* oth of 1700. Ran 53 joints (1673') temented first stage with 382 cubic el & 1/4# flocele. Tail in with L.2. Plug down at 9:00 am on 9-13-83.
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Secretary (This space for Federal or State of	DATE September 15, 1983
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
CONDITIONS OF AFFROYAL, IF ANT.	ACCEPTED FOR RECORD

*See Instructions on Reverse Side

SEP 22 1983

 • •	
Budget Bureau No. 42-R14	12
 	_

UNITED STATES	
DEPARTMENT OF THE INTERIOR	5. LEASE NM-03179
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
1 -11	Aztec
well well other	9. WELL NO. #10
2. NAME OF OPERATOR Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Drawer 570, Farmington, NM 87499	Kutz Fruitland
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA
below.) 1040' FNI & 965' FFI	Section 14, T28N, R11W
AT SURFACE: 1040 1112 & 603 FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD 5760' GL
REPAIR WELL	(NOTE: Report results of multiple completion or zon change on Form 9–330.)
CHANGE ZONES	directionally drilled, give subsurface locations and ent to this work.)* on 9-11-83 and drilled to 248'. ing at 240'.
CHANGE ZONES ABANDON* (other) Spud & casing Report X CORRECTED 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing stating and statin	ate all pertinent details, and give pertinent dates directionally drilled, give subsurface locations and ent to this work.)* on 9-11-83 and drilled to 248'. Ing at 240'.
CHANGE ZONES ABANDON* (other) Spud & casing Report X CORRECTED 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing state of the complex of the	ate all pertinent details, and give pertinent dates directionally drilled, give subsurface locations and ent to this work.)* If on 9-11-83 and drilled to 248'. Ing at 240'. OCT -6 1983 OCT -6 1983 Set @F
CHANGE ZONES ABANDON* (other) Spud & casing Report X CORRECTED 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing set 5 joints (227') of 8-5/8", 24# casing subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct signed sharpy surface Safety surface Safety Safety surface Safety Saf	ate all pertinent details, and give pertinent dates directionally drilled, give subsurface locations and ent to this work.)* If on 9-11-83 and drilled to 248'. Ing at 240'. Set @
CHANGE ZONES ABANDON* (other) Spud & casing Report X CORRECTED 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 11-83 Spudded 12-1/4" surface hole at 3:00 am Set 5 joints (227') of 8-5/8", 24# casing state of the complete of the casing subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	ate all pertinent details, and give pertinent dates directionally drilled, give subsurface locations and ent to this work.)* If on 9-11-83 and drilled to 248'. Ing at 240'. Ing at 240'. DIST. 3 Set @F

*See Instructions on Reverse Side

OCT 04 1983

FARMINGTON RESOURCE AREA
BY