

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED  
BLM

97 FEB 20 11:12:22

070 FARMINGTON, NM

5. Lease Designation and Serial No.

I - 149 - IND - 8472

6. If Indian, Allottee or Tribe Name

NAVAJO

7. If Unit or CA, Agreement Designation

8. Well Name and No.

GALLEGOS CANYON UNIT 156E

9. API Well No.

3004526234

10. Field and Pool, or Exploratory Area

BASIN DAKOTA

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Nancy I. Whitaker

3. Address and Telephone No.

P.O. BOX 800 DENVER, COLORADO 80201

303-830-5039

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850 FSL

790 FWL

Sec. 26 T 28N R 13W

UNIT L

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☒ Casing Repair  
☐ Altering Casing  
☒ Other RE-PERFORATION

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRUSU 1/20/97

NUBOP & TEST. TALLY TBG OUT OF HOLE. TIH W/RBP SET AT 6230'. DUMPED SAN ON PLUG 6220 - 6230'. PRESSURE TESTED CASING TO 500 PSI FOR 5 MINUTES. DIDN'T HOLD. PLUG TESTED TO 1000 PSI. ISOLATED HOLE IN CASING AT 3449' TO 3459'. SQUEEZED 75 SXS, 15 BBLS CLASS B CEMENT @ 1 BPM. RELEASED PKR & TOH W/ PKR AND TIH W/6.75" BIT, SCRAPER TAGGED CEMENT AT 3350'. DRL CEMENT TO 3538'. PRESSURE TESTED SQUEEZE, BLED DN TO 0 IN 18 MIN. RU TO SWAB TO 1800 FOR NEG TEST. SWABBED TO 3640 W/O FLUID ENTRY. SIFN. FLUID LEVEL @ 1900' TOH W/TBG & TIH W/ PKR SET AT 3323'. PUMPED 31 BBLS, 150 SXS OF CLASS B NEAT. TIH W/BIT & SCRAPER & TAGGED CMT. DRILLED TO 3567'. PRESSURE TESTED CSG TO 200 PSI FOR 30 MINUTES. HELD OKAY. CIRCULATED AND C/O SAND WITH NITROGEN & FOAM. TOH WITH RBP TIH WITH 2 3/8" TBG & SN LNDED AT 6335'. SWABED AND TAG FLUID AT 6300'. TOH. TIH WITH TBG. LNDED AT 6350 W/ SN AT 6318'. C/O TO BOTTOM WITH NITROGEN AND FOAM. TOH WITH TBG. TIH W/LOG RAN GR. REPERFORATED BASIN DAKOTA, 6271 - 6281 & 6332 - 6366' WITH 2 JSPF, .450 DIA. 120 DEG PHASING 19.5 GMS CHARGE. TIH WITH 2 3/8" TBG. LANDED AT 6350' AND SN AT 6318'. SWABBED WELL 6 RUNS FLOWED & SWABBED 48 BBLS TO TANK. WELL KICK OFF.

RDSUMO 2/7/97

14. I hereby certify that the foregoing is true and correct

Signed Nancy I. Whitaker

Title

Staff Assistant

Date

02-17-1997

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

MAR 05 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

FARMINGTON DISTRICT OFFICE