No.

No.

No.

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55 MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS Pool Blanco ____Formation___ Mess Verde County Rio Arriba Initial XX Annual Special Date of Test 7-31-58 CompanyPACTITE NORTHYPET PIPELING Lease San Jum 29-6 Well No. 50-36 Unit <u>H</u> Sec. 36 Twp 29 Rge. 6 Purchaser Casing 56" Wt. I.D. Set at 5685' Perf. 5166' To 5650' Tubing 1-1/h Wt. I.D. Set at 5642 Perf. To Gas Pay: From To L xG.650 GL Bar. Press. 12 Producing Thru: Casing XXX Tubing Type Well Single

Single-Bradenhead-G. G. or G.O. Dual Date of Completion: Packer Reservoir Temp. OBSERVED DATA Tested Through (Proyet) (Choke) (Never) Shut in 7 days Type Taps Flow Data Tubing Data Casing Data Diff. Temp. (Prover) (Choke) Press. Press. Temp. Press. Temp. Duration (Line) (Orifice) of Flow \circ_{F} \circ_{F} . $^{\circ}F$. Size Size psig psig $h_{\mathbf{w}}$ psig Hr. 1102 1104 68 3/4 526 3 hours **601** 526 FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow Factor **Factor** Factor Q-MCFPD Fg $\mathbf{F_t}$ (24-Hour) $F_{\boldsymbol{p}\underline{\boldsymbol{v}}}$ ${\bf h_{w}p_{f}}$ psia @ 15.025 psia 1.053 12.3650 538 .9924 .9608 6679 PRESSURE CALCULATIONS Gravity of Liquid Hydrocarbons cf/bbl. deg. Specific Gravity Separator Gas Specific Gravity Flowing Fluid ____deg. (1-e^{-s}) P_{c} 1116 P_{c}^{2} 1245.5 $P_{\mathbf{w}}$ 613_{Pw2} $(\mathbf{F_cQ})^2$ P₊2 $(F_cQ)^2$ $P_c^2 - P_w^2$ F_cQ $\frac{P_{\boldsymbol{W}}}{P_{\boldsymbol{C}}}$ Cal. Pt (psia) 869.1 1.43 376.4 MCFPD; n .75/ 1.3077 Absolute Potential: 8,734 COMPANY PACIFIC NORTHWEST PIPELINE CORPORATION ADDRESS 418 West Broadway, Farmington, New Mexico AGENT and TITLE C. R. Namer - Well Test Engineer WITNESSED COMPANY REMARKS AUG 5 1958 OIL CON. COM.

DIST. 3

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received		
DISTRIBUTION		
	NO.	
Operator		
Sagts Fe.	1	
Proration Office	f +	<u></u>
State Land Office		
U. S. G. S.	/	
Transporter		
Pile		v