

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079761-A
Unit San Juan 29-4 Unit
14-00-001-1055

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

RECEIVED
DEC 2 1959
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER ACTION)

December 1, 1959

Well No. 11-33(10) is located 1500 ft. from N line and 810 ft. from E line of sec. 33

N2/4 Sec. 33 (1/4 Sec. and Sec. No.) 2N2E (Twp.) 10W (Range) T14N R10E (Meridian)


Blanco N.V. & Wilcox Dak. (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7375 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 11-29-59 C.T.D. 9306'. Perf. Lower Dakota 8704-8710; 8714-8724 (2 DJ/ft.) acidized w/500 gal. MCA (15%).
- 11-30-59 Set Baker cast iron retainer at 8700'. Squeezed Lower Dakota perfs. w/50 sacks Formix "140". Final pressure 4000#.
- 11-30-59 Perf. Upper Dakota 8670-78; 8682-8692 (2 DJ/ft.) acidized w/500 gal. 15% MCA.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 271

Farmington, New Mexico

By ORIGINAL SIGNED H.E. McANALLY

Title Petroleum Engineer