


Form 9-331a
(Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **079760**
Unit **San Juan 29-4 Unit**
14-08-001-1055

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 23, 19 58

Well No. **15-25** is located **1650** ft. from **[N]** line and **1650** ft. from **[E]** line of sec. **25**
NS **Sec. 25** **29N** **4W** **N.M.P.M.**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Chosa Mesa P.C. **Rio Arriba** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is **7003** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended to plug and abandon this well in the following manner:

1. Squeeze perf. w/50 sks. regular cement.
2. Shoot 5 1/2" casing @ 2700' and pull.
3. Set cement plug w/10 sks. on stub.
4. Set cement plug w/75 sks. from 1000' to 1200'.
5. Set cement plug at surface w/10 sks.
6. Set 4' x 4" marker.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**

Farmington, New Mexico

By **Original Signed D. W. Meehan**

Title **Petroleum Engineer**