3-MACC Axtec 1-Rill Cutler

1-Oliver Fowler 1-Smith

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Form C-122 Revised 12-1-55

1-File Pool **Elenco** Formation Kess Verde County Rio Arriba Initial XX Annual Special \_\_\_ Date of Test 6/25/58 Company PACIFIC HORTHWEST PIPELINE Lease San Juan 29-6 Well No. 42-25 Unit H Sec. 25 Twp 23H Rge. 6W Purchaser Est connected Casing 53" Wt. I.D. Set at 5950 Perf. 5354 To 5924 Tubing 1-1/4" Wt. 2.3 I.D. Set at 5883' Perf. To Gas Pay: From To L xG .650 GL Bar. Press. 12 Producing Thru: Casing Tubing Tubing Tubing Single-Bradenhead-G. G. or G.O. Dual Date of Completion: 6-16-58 Packer Reservoir Temp. OBSERVED DATA Tested Through (Choke) (Choke) Shut in 9 days Type Taps Flow Data Tubing Data Casing Data (Prover) (Choke) Diff. Temp. Press. Press. Temp. Press. Temp. Duration No. (Orifice) (Line) of Flow Size Size psig oF. o<sub>F</sub>. °F•  $h_{\mathbf{W}}$ psig psig Hr. 1097 1089 3/4" 50 135 135 3 hours FLOW CALCULATIONS Coefficient Pressure Flow Temp. Gravity Compress. Rate of Flow No. Factor Factor Q-MCFPD Factor  $\mathbf{F}_{\mathbf{g}}$  $\textbf{h}_{\boldsymbol{w}}\textbf{p}_{\mathbf{f}}$ (24-Hour)  $F_{\mathbf{t}}$  $F_{p\underline{\boldsymbol{v}}}$ psia @ 15.025 psia 12.3650 1.0098 .9666 1.014 1788 PRESSURE CALCULATIONS cf/bbl. Gas Liquid Hydrocarbon Ratio Specific Gravity Separator Gas Fravity of Liquid Hydrocarbons \_\_\_\_\_deg. Specific Gravity Flowing Fluid\_\_\_\_ \_\_\_\_(1-e<sup>-s</sup>) P<sub>c</sub> 1100 P<sub>c</sub> 1212.2  $P_{\mathbf{w}}$  $(\mathbf{F_c}\mathbf{Q})^2$  $P_c^2 - P_w^2$ P<sub>t</sub>.  $(F_cQ)^2$  $F_cQ$ No. Cal. (1-e-s) Pt (psia)  $P_{\underline{\mathbf{w}}}$ 917.8 20k. h 4.12 MCFPD; n\_\_\_\_\_.75/ 2.8917 5,170 Absolute Potential: COMPANY PACIFIC BORTHWEST PIPELIE COMPONENTS ADDRESS 1981 West Breadery, Breader, New Medica AGENT and TITLE C. R. Wagner - Well Test Engineer WITNESSED COMPANY REMARKS OIL CON. COM

Clar. 3

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- $P_{w}$  Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_{f}$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- F<sub>DV</sub> Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\rm W}$  cannot be taken because of manner of completion or condition of well, then  $P_{\rm W}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\rm t}$ .

AZTEO D	STE		FICE	
Paul Lega Rec	<b>Serv</b> ed	. <b>G</b>		
en e			Control of the Contro	
n Terekatan		enter Profesion		
From Attorn Carrons	-	/		
15 - 23 25 25 25 25 25 25 25 25 25 25 25 25 25				
Transporter			·	ne errore ar kann
F116	ĺ	1		-