3 - HMOCC 1 - State Land Office

1 - L. G. Truby

1 - File

Form C-103 (Revised 3-55)

NEW MEXICO OIL CONSERVATION COMMISSION MISCELLANEOUS REPORTS ON WELLS

(Submit to appropriate District Office as per Commission Rule 1106)

POOL Blanco Mesa Verde Results of Test of Casing Shut-off Remedial Work X Other Report of Water Shut-off httity of materials used and results obtained to the shurry 244 cubic ft. Approximate to formation temp. 70°F. Estimated strength place 12 hrs. before test. Casing tested Ca
Results of Test of Casing Shut-off Remedial Work Tother Report of Water Shut-off Intity of materials used and results obtained to the shurry 244 cubic ft. Approximate to formation temp. 70°F. Estimated strength place 12 hrs. before test. Casing tested
Results of Test of Casing Shut-off Remedial Work Tother Report of Water Shut-off Intity of materials used and results obtained to the shurry 244 cubic ft. Approximate to formation temp. 70°F. Estimated strength place 12 hrs. before test. Casing tested
Results of Test of Casing Shut-off Remedial Work The Complete of Water Shut-off At the Report of Water Shut-off Intity of materials used and results obtained to the communication of the communication temp. 70°F. Estimated strength place 12 hrs. before test. Casing tested of the communication of the communication temp. 70°F. Estimated strength place 12 hrs. before test. Casing tested of the communication of the complete of the complete of the communication of the
Remedial Work X Other Report of Water Shut-off ntity of materials used and results obtained 4", H-40, 32.75# easing 8 190.00", cemented f cement slurry 244 cubic ft. Approximate ted formation temp. 70°F. Estimated strengt place 12 hrs. before test. Casing tested 0 815.60", cemented w/150 ax Portland regular egular w/25 CaCle plus if flocele per ax. tested 0K. 00", Baash-Ross liner hanger 8 3716.00", 100 ax Portland regular w/45 gel plus ore test. Pressured to 2500%, held 0K. ORTS ONLY cod. Int. Compl Date
A Other Report of Water Shut-off ntity of materials used and results obtained A", H-40, 32.75# easing @ 190.00', cemented f cement slurry 244 cubic ft. Approximate ted formation temp. 70°F. Estimated strength place 12 hrs. before test. Casing tested 08 815.60', cemented w/150 ax Portland regular egular w/25 CaCle plus if flocele per sx. tested 0K. 00', Baash-Ross liner hanger @ 3716.00', 100 ax Portland regular w/45 gel plus if ore test. Pressured to 2500%, held 0K. ORTS ONLY
A Other Report of Water Shut-off ntity of materials used and results obtained A", H-40, 32.75# easing @ 190.00', cemented f cement slurry 244 cubic ft. Approximate ted formation temp. 70°F. Estimated strengt place 12 hrs. before test. Casing tested 0 815.60', cemented w/150 ax Portland regular egular w/25 CaClo plus if flocele per sx. tested 0K. 00', Baash-Ross liner hanger @ 3716.00', 100 ax Portland regular w/45 gel plus if ore test. Pressured to 2500%, held 0K. ORTS ONLY
htity of materials used and results obtained 4", H-40, 32.75# easing 8 190.00', cemented f cement slurry 244 cubic ft. Approximate ted formation temp. 70°F. Estimated strengt place 12 hrs. before test. Casing tested 0 815.60', cemented w/150 ax Portland regular egular w/25 CaClo plus 15 flocele per sx. tested 0K. 00', Baash-Ross liner hanger 6 3716.00', 100 ax Portland regular w/45 gel plus ore test. Pressured to 25007, held 0K. ORTS ONLY cod. Int Compl Date
4", H-40, 32.75# casing 8 190.00', cemented f cement slurry 244 cubic ft. Approximate ted formation temp. 70°F. Estimated strengt place 12 hrs. before test. Casing tested 0.815.60', cemented w/150 sx Portland regular egular w/25 CaClo plus 15 flocele per sx. tested 0K. 00', Baash-Ross liner hanger 6 3716.00', 100 sx Portland regular v/45 gel plus 15 ore test. Pressured to 25005, held 0K. ORTS ONLY
f ement slurry 244 cubic ft. Approximate ted formation temp. 70°F. Estimated strengt place 12 hrs. before test. Casing tested 0.815.60', emented w/150 ax Portland regular egular w/25 CaClo plus if flocele per sx. tested 0K. 00', Baash-Ross liner hanger 6 3716.00', 100 ax Portland regular w/45 gel plus if ore test. Pressured to 2500f, held 0K. ORTS ONLY cod. Int Compl Date
od. IntCompl Date
ring Dia Oil String Depth
ormation (s)
BEFORE AFTER
DM.
/
(Company)
ereby certify that the information given we is true and complete to the best of
ne Original signed by L. r. Stone
sition Division Manager
mpany Pacific Monthwest Pipeline Corp.

101221	TION COMM	OIL CONSERVA
	TPICT OFFIC	
		No. Copies Rec
OPTRIBUTION		
	NO.	
-	/	Operato:
		Santa he
		Profesion Color
		State Land Office
		U. S. G. S.
		Transporter
/ -	1	File

•