Form C-122

	1 - F1	70	·	ህጠ ጥፐ	_DATNT D/	ירע מסבים	יים אמונים	T FOR GAS	WELLS]	Revised 12-1-5	
oo'	Rlane	•								Rio A	rriba	
11t	lai		Annua	3.1	Corp.,	spec	:1a1		_bate or	1. 17.	1-17-59	
omp	any Pacifi	e No	et hue	st P1	peline !	ease		29-5	weı	T NO	31-29	
nit	7 5/8"	ec	29 Twi	- 29	₩ Rge	• <u>5¥</u>	Purc 3885	haser	let Conr	ected	6026	
ıbi	ng 1 W	t	<u>.</u> I.	.D1	38 Set	at_60	15 Pe	rf	6012	To	6015	
is	Pay: From_	5496	To	6026_	L		.G650	GL		Bar.Pre	ss <u>12</u>	
od	ucing Thru:	Cas	sing_		Tul	oing	XXX	Type We	11	ingle	O Dual	
Date of Completion:					Si • Packer			Type Well ingle-Bradenhead-G. G. or G.O. Dual Reservoir Temp.				
	•						ED DATA					
								าร				
								Tubing Data				
Т	(Prover)	(Che	Flow Da	Press	. Diff.	Temp.			Casing I	Temp.	Duration	
٥٠	(Line) Size	(Ori	fice) ize	psig	h _w	\circ_{F} .	psig	o _F .	psig	o _F ∙	of Flow Hr.	
1					1		1087		1085	ļ <u>-</u>		
7		3/	1	149		480	149	A9 [®]	<u>949</u>			
										 		
	· · · · · · · · · · · · · · · · · · ·											
							CULATION				Data of Flore	
,	(24-Hour)		nt		ressure	Flow Temp. Factor Ft		Gravity Factor	Compress. Factor Fpv		Rate of Flow Q-MCFPD @ 15.025 psia	
			$\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$		psia			Fg				
	12.3650				161	1.011	7	.9608	1.01	7	1968	
\exists												
工											<u></u>	
					PR	ESSURE (CALCU ATI	ONS				
	iquid Hydro					cf/bbl					arator Gas wing Fluid	
								1099 Pc 1207.8				
	-											
0.	$P_{\mathbf{w}}$	P	2 F	_c Q	$(F_cQ)^2$	(1	F _c Q) ²	961 P. 2	P _c -P _w ²	Ca	al. Pw	
	Pt (psia)		t 1	c ·	\- C-0		l-e-s)	w		1	Pw Pc	
								923.5	284.3		4.25	
:												
	olute Potent	_		895_		MCFPD		/2.9599				
DDF	RESS	1841		Brood Filmod	Tipel	amo-00 areles	rpereti ten, Ke	w Nexte	———			
JEN Vivi	NT and TITLE NESSED	<u> </u>	C. R.	-Nega	or Ve	11 Tes	t Ingin	•••				
	PANY			- 			MARKS		/A)			

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_{w} Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

OIL CONSERVAT	TION COMMIS	SION								
AZTEC DISTRICT OFFICE										
No. Copies Received										
DISTRIBUTION										
	NO.									
Carrestor	1									
5.002 00										
Groration (#1)										
rate Land Office	en e									
S. G. S.										
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1	1								