


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079893-A
Unit San Juan 29-4 Unit
14-00-001-1055

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 4, 1957

Well No. 13-29 is located 1450 ft. from {N} line and 1140 ft. from {E} line of sec. 29

NE Sec. 29

(1/4 Sec. and Sec. No.)

29N

(Twp.)

4W

(Range)

N.M.P.M.

(Meridian)

Blanco

(Field)

Rio Arriba

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 7352 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

11-30-57 to 12-2-57 Total depth 6583'.

This well was plugged and abandoned in the following manner:

1. Set cement retainer at 5542' and squeezed Mesa Verde perforations at 6152-6509 (in 5 1/2" liner) with 100 sacks cement. Left retainer in liner as permanent bridge plug.
2. Found free point in 7 5/8" casing at 1108', cut casing off at 1106' and pulled 26 joints. Top of cement behind 7 5/8" casing was at 3950' which is above the top of the Pictured Cliffs (4182') formations.
3. Set plug at 1050'-1106' with 25 sacks cement (top of 7 5/8" intermediate casing).
4. Set plug at 468-668' with 110 sacks cement.
5. Set plug at 100'-160' with 25 sacks cement (bottom of 10 3/4" surface casing).
6. Set plug at surface with 25 sacks cement.
7. Set 4" pipe 4' high at surface as permanent marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas CompanyAddress Box 997Farmington, New MexicoBy Original Signed D. C. JohnsonTitle Petroleum Engineer