DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLSON, COM. DIVICE OF INTERIOR TO DRILL. SUBSCUENT REPORT OF WATER SUIT-OFF. SUBSCUENT REPORT OF WATER SUIT-OFF. SUBSCUENT REPORT OF SOUTHING ACADEMY. SUBSCUENT REPORT OF SOUTHING. SUBS			Uniti	ED STATES	Lease No
SUNDRY NOTICES AND REPORTS ON WELLSON, COM. DITIES OF INTENTION TO DRILL DITIES OF INTENTION TO CHANGE PLANS. DITIES OF INTENTION TO TEST WATER SHIT-OFT. SUBSEQUENT REPORT OF SUPPLINES OR ACIDIZING. SUBSEQUENT REPORT OF ALTRENG CASING. DITIES OF INTENTION TO SHOOT OR ACIDIZING. SUPPLINESTORY OF SECRETIAN OR REPAIR WILL. SUBSEQUENT REPORT OF ALTRENG CASING. SUPPLINESTORY OF ALTRENG OR ACIDIZING. SUPPLINESTORY OF ALTRENG CASING. SUPPLINESTORY OF ALTRENG CAS	1-		DEPARTMENT	OF THE INTERIOR	Unit
SUNDRY NOTICES AND REPORTS ON WELLSON, COM- DITICE OF INTENTION TO DRILL. DITICE OF INTENTION TO CHANGE FLAMS. SURREQUEST REPORT OF SHOOTING OR ACCIDIZATION SURREQUEST REPORT OF ALTERING CASING. SUBSCUENT REPORT OF ALTERING CASING. SUBSCUENT REPORT OF SHOOTING OR REPAIR WILL SUBSCUENT REPORT OF ALTERING CASING. SUBSCUENT REPORT OF ALTERING. SUBSCUENT REPORT OF ALTERING CASING. SUBSCUENT REPORT OF AL			GEOLOG	SICAL SURVEY	
SUNDRY NOTICES AND REPORTS ON WELLSON, COM- DITICE OF INTENTION TO DRILL. DITICE OF INTENTION TO CHANGE FLAMS. SURREQUEST REPORT OF SHOOTING OR ACCIDIZATION SURREQUEST REPORT OF ALTERING CASING. SUBSCUENT REPORT OF ALTERING CASING. SUBSCUENT REPORT OF SHOOTING OR REPAIR WILL SUBSCUENT REPORT OF ALTERING CASING. SUBSCUENT REPORT OF ALTERING. SUBSCUENT REPORT OF ALTERING CASING. SUBSCUENT REPORT OF AL					1 Million V
SUBSCOUNT REPORT OF WATER SHIT-OF SUBSCOUNT REPORT OF WATER SHIT-OF SUBSCOUNT REPORT OF SHOTING OR ACIDIZING SUBSCOUNT REPORT OF SHOTING OR ACIDIZING SUBSCOUNT REPORT OF ACADIOMISM SUBSCOUNT REPORT OF ACIDIZING SUBSCOUNT REPORT OF ACADOMISM SUBSCOUNT REPORT OF					1 444 1 1 1958
SUBSCOUNT REPORT OF SCOTTING OR ACIDIZING. SUBSCOUNT REPORT OF SCOTTING OR ACIDIZING. SUBSCOUNT REPORT OF SCOTTING OR ACIDIZING. SUBSCOUNT REPORT OF REPORT OF ACIDIZING. SUBSCOUNT REPORT OF REPORT OF REPORT. SUBSCOUNT REPORT OF REPORT OR REPORT. SUBSCOUNT REPORT OF READMOND. SUBSCOUNT REPORT OF ALEXANG. SUBSCOUNT REPORT. SUBS		SUNDRY	NOTICES A	ND REPORTS OF	WELLS ON COM.
SUBSCOUNT REPORT OF SHOUTING OR ACIDIZING. SUBSCOUNT REPORT OF SHOUTING OR ACIDIZING. SUBSCOUNT REPORT OF ALTERING CASING. SUBSCOUNT REPORT OF ALTERING CASING. SUBSCOUNT REPORT OF ALTERING CASING. SUPSCOUNT REPORT OF ALTERING OR REPAIR WILL. SUBSCOUNT REPORT OF ALTERING CASING. SUPSCOUNT REPORT OF ALTERING CASING. SUBSCOUNT REPORT OF ALTERING CASING. SUPSCOUNT REPORT OF ALTERING CASING. SUBSCOUNT REPORT OF ALTERING CASING. SUPSCOUNT REPORT OF ALTERING CASING. THE THE TOTAL OF ALTERING CASING. SUPSCOUNT REPORT OF ALTERING CASING. SUPSCOUNT REPORT OF ALTERING CASING. THE THE TOTAL OF ALTERING CASING. THE THE THE TOTAL CASING. SUPSCOUNT REPORT OF ALTERING CASING. THE THE TOTAL OF ALTERING CASING. THE THE THE TOTAL CASING. SUPSCOUNT REPO	OTICE OF INT	TENTION TO DON'T			0.2.003
SUBSCOURT REPORT OF ALTERING CASING. SUPPLEMENTARY WELL HISTORY. SUPPLEMENTARY. WELL HISTORY. SUPPLEMENTARY. SUPPLEMENTARY. WELL HISTORY. SUPPLEMENTARY. SUPPLEMENTARY. WELL HISTORY. SUPPLEMENTARY. SUPPLEMENTARY. SUPPLEMENTARY. SUPPLEMENTARY. SUPPLE				li e	·
SUBSCOURN REPORT OF RE-DRILLING OR REPAIR SUBSCOURN REPORT OF RE-DRILLING SUBSCOURN REPORT OF RE-DRILLING SUBSCOURN REPORT OF RE-DRILLING SUBSCOURN RE				l#	
SUBSCOUNT REPORT OF ARADONMENT. STREET OF INTENTION TO PAUL OR ALTER CASING. STREET OF INTENTION TO ARADON WELL. (INDICATE AROVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) S. J. 29-6 that: INO. 60-18 is located 1800 ft. from. In line and 810 ft. from E line of sec. 18 (IN 20-18 is located 1800 ft. f				ll e	
SUPLEMENTARY WELL HISTORY. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) ***PLY State** No. 60-15 is located 1800 ft. from ine and 10 ft. from ine of sec. 18			1	13	; I
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Jaly Sta. 19-6 that No. 60-18 is located 1800 ft. from No. line and 10 ft. from No. line of sec. 18 // Mar/h Hee. 18 29 Horth 6 thest H.M.P.H. (If No. and So. No.) (Pup.) (Range) (Mortdian) Blue Bautice (Field) (County or Subdivision) (State or Turritory) celevation of the deliverable above sea level is 33h ft. DETAILS OF WORK a names of and expected depths to objective ands; show sizes, weights, and laughts of proposed casings; indicate mudding jobs, camentoling points, and all other important proposed work) a names of and expected depths to objective ands; show sizes, weights, and laughts of proposed casings; indicate mudding jobs, camentoling points, and all other important proposed work) a names of and expected depths to objective ands; show sizes, weights, and laughts of proposed casings; indicate mudding jobs, camentoling points, and all other important proposed work) a names of and expected depths to objective and all other important proposed casings; indicate mudding jobs, camentoling points, and all other important proposed casings; indicate mudding jobs, camentoling June 1975, Ed. Oct. 2000 and Fortile and 1975 and 19	OTICE OF INT	ENTION TO PULL OR	ALTER CASING	(I	
S.J. 29-6 Unit Il No. 60-18 is located 1800 ft. from Nine and 810 ft. from E line of sec. 18 // He/4 sec. 18 29 Sorth 6 thet H. 18-18. (It Sec. and Sec. No.) (Twp.) (Range) (Meridian) Every North State of S	OTICE OF INT	TENTION TO ABANDON	WELL		
S.J. 29-6 Unit Il No. 60-18 is located 1800 ft. from Nine and 810 ft. from E line of sec. 18 // He/4 sec. 18 29 Sorth 6 thet H. 18-18. (It Sec. and Sec. No.) (Twp.) (Range) (Meridian) Every North State of S					
is located 1800 ft. from No. 18 1800 ft. from No. 1800 ft. from No. 1800 ft. from No. 1800 ft. ft. DETAILS OF WORK a names of and expected depths to objective aneign show sizes, weights, and laugths of proposed casings; indicate mudding jobs, comentaling points, and all other important proposed work) a names of and expected depths to objective aneign show sizes, weights, and laugths of proposed casings; indicate mudding jobs, comentaling points, and all other important proposed work) a names of and expected depths to objective aneign show sizes, weights, and laugth of proposed casings; indicate mudding jobs, comental visual fines and in the important proposed work) a names of and expected depths to objective aneign and show sizes and in the important proposed work) a names of and expected depths to objective aneign and show sizes are sizes and sizes and sizes are sizes and sizes and sizes are sizes and sizes and sizes and sizes are sizes and sizes and sizes are sizes and sizes and sizes and sizes are sizes and sizes and sizes are sizes and sizes and sizes and sizes are sizes and si		(INDICA	FE ABOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE, OR OTHER	R DATA)
Il No. 60-18 is located 1800 ft. from No. 60-18 is located 1800 ft. ft. 60-18 (Field) (County of Subdivision) (State or Territory) see elevation of the definition of the definiti				Jul	y 8th, 19 58
(i) Sec. and Sec. No.) (ii) (County or Subdivision) (Field) (County or Subdivision) (Classo or Territory) (Cl					, , , , , , , , , , , , , , , , , , ,
(i) Sec. and Sec. No.) (ii) (County or Subdivision) (Field) (County or Subdivision) (Classo or Territory) (Cl	ll No.	o-18 is locat	ed 1800 ft. from	N line and 610 ft fr	om E line of sec.
(Here and Sec. No.) (Twp.) (Range) (Here and Sec. No.) (Field) (County or Subdivision) (State or Territory) (State or Territory) (County or Subdivision) (State or Territory) (State or Territory) (County or Subdivision) (State or Territory) (County or Subdivision) (State or Territory) (State or Territory) (County or Subdivision) (State or Territory) (State or Territory) (State or Territory) (County or Subdivision) (State or Territory) (S			oa	inc and	inie or sec.
(Field) (County or Subdivision) (State or Territory) ground (County or Subdivision) (State or Territory) ground (County or Subdivision) celevation of the derivatives above sea level is	J		29 North 6	idet H.H.P.K.	
c elevation of the derivatives above sea level is		•		· ·	·
celevation of the defree most above sea level is					New Mexico
DETAILS OF WORK a names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) midded June 19th, 1956. Set 180.98° of 18-1/4", 32.75%, 3-h0 easing a 192.98°, married w/200 ax Portland regular w/36 Caci. Volume of coment slarry sho on. 74 premiumte temp, of coment always when sized 60°?. Estimated formation temp. 7. Intimated strength of coment 5775% per square inch. Coment was in place have before test, tested (8. 1 1398° of 7-5/8", 26.40%, 3-55 casing a 3h10°, comented w/150 ax Portland regular sized of 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575°, lines hanges a 333h.16°, comented to 200.86° of 5-1/8", 16.5%, 3-55 lines hanges a surface has before test, pressured to 200.86° of 5-1/8", 16.5%, 3-55 lines a 575° of 16.5% of 5-1/8", 16.5% of 5-1/8	,-	(STORE)	(County of L		(State of Territory)
a names of and expected depths to objective sands; show sizes, weights, and longths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) maked June 19th, 1956. Set 180.98° of 18-1/h", 32.79¢, E-10 casing a 162.98°, numbed w/300 ax Portland regular w/36 CaCl. Volume of cament always who as precision to temp. of cament always when mined 60°7. Estimated formation temp. 7. Estimated strength of cament 8773¢ per agence inch. Coment was in place has before test, tested CE. 1 335° of 7-5/8°, 36-10¢, 3-55 casing 8 3110°, camented w/150 ax Portland regular 25 gai and 30 samest w/36 CaCl. Coment was in place 3hirs before test, tested of 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines a 10°, 10°, 10°, 10°, 10°, 10°, 10°, 10°,	e elevation	n of the derries	above sea leve	l is 6334 ft.	
a names of and expected depths to objective sands; show sizes, weights, and longths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) maked June 19th, 1956. Set 180.98° of 18-1/h", 32.79¢, E-10 casing a 162.98°, numbed w/300 ax Portland regular w/36 CaCl. Volume of cament always who as precision to temp. of cament always when mined 60°7. Estimated formation temp. 7. Estimated strength of cament 8773¢ per agence inch. Coment was in place has before test, tested CE. 1 335° of 7-5/8°, 36-10¢, 3-55 casing 8 3110°, camented w/150 ax Portland regular 25 gai and 30 samest w/36 CaCl. Coment was in place 3hirs before test, tested of 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges 6 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines a 5573°, lines hanges a 3354.16°, camented 3 2810.86° of 5-1/2°, 16¢, 3-55 lines a 5573°, lines a 10°, 10°, 10°, 10°, 10°, 10°, 10°, 10°,					
mided June 19th, 1958. Set 180.98' of 19-3/4", 32.756, X-hO ensing @ 192.98', namical v/200 ax Portland regular v/36 CaCl. Volume of cament slurry Shh on. It presiming temp. of cament always when mind 60°7. Estimated formation temp. 17. Retirects strength of cament 27756 per square inch. Omment was in place has before test, tested CK. 1398' of 7-5/8", 36.hof, 3-55 casing @ 3h10", camented v/150 ax Portland regula 15 gal and 90 cament v/85 CaCl. Coment was in place Shire before test, tested of 1 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 2800.8h' of 5-1/8", 186, 3-55 liner @ 3575", liner hanger @ 335h.16", camented 2 335h.16", camented 3 33					
maked June 19th, 1958. Set 180.98' of 18-1/h", 32.75#, E-hO easing @ 198.98', manufed w/200 ax Portland regular w/36 CaCl. Tolume of cament alarry 2hh on. It presimpts temp. of cament alarry when mined 60°P. Estimated formation temp. To. Retianated strength of cament 2575# per square inch. Cament was in place has before test, tested Ca. 1 3398' of 7-5/8", 26.50#, 3-55 easing @ 3h10', camented w/150 ax Portland regular 198 gal and 90 amount w/25 CaCl. Commit was in place Shire before test, tested a 2500.84' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.84' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.84' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 184, 3-55 lines @ 5575', lines hanges @ 3358.16', camente 1250.85' of 5-1/2", 1857', lines hanges @ 3358', lines hanges @ 33	te names of a	nd expected depths to	objective sands; show sizes, ing points, and all oth	weights, and lengths of proposed car or important proposed work)	sings; indicate mudding jobs, cement-
President temp. of count always that mind 60°7. Betimeted fermation temp. 7. Retimeted strength of count \$5775° per square inch. Coment was in place are before test, tested Cf. 1 3390° of 7-5/8°, 26.10°, 3-55 coming 8 3110°, comented v/150 ex Portend regal. 15 gal and 50 samest v/8° CaCl. Coment was in place Share before test, tested to 2500.8° of 5-1/2°, 10°, 3-55 liner c 5575°, liner hanger 6 3351.16°, comented to 2500.8° of 5-1/2°, 10°, 3-55 liner c 5575°, liner hanger 6 3351.16°, comented as Portland regular v/0° gal place of flacele per ax. Coment was in place has before test, pressured to 2500°, held Ck. The plan of work must receive approval in writing by the Geological Survey before operations may be commenced. PACIFIC HORTHWEST PERMITTER CORPORATION Tester by Contact by Goo. 2. Popple By Criginal signed by Goo. 2. Popple Title District Protestion Engineer					
President temp. of count always that mind 60°7. Betimeted fermation temp. 7. Retimeted strength of count \$5775° per square inch. Coment was in place are before test, tested Cf. 1 3390° of 7-5/8°, 26.10°, 3-55 coming 8 3110°, comented v/150 ex Portend regal. 15 gal and 50 samest v/8° CaCl. Coment was in place Share before test, tested to 2500.8° of 5-1/2°, 10°, 3-55 liner c 5575°, liner hanger 6 3351.16°, comented to 2500.8° of 5-1/2°, 10°, 3-55 liner c 5575°, liner hanger 6 3351.16°, comented as Portland regular v/0° gal place of flacele per ax. Coment was in place has before test, pressured to 2500°, held Ck. The plan of work must receive approval in writing by the Geological Survey before operations may be commenced. PACIFIC HORTHWEST PERMITTER CORPORATION Tester by Contact by Goo. 2. Popple By Criginal signed by Goo. 2. Popple Title District Protestion Engineer		1912, 19	70. Act 150.55	es 10-3/4", 32.75¢,	2-40 mains @ 192.98',
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer		MANON BE FOR	ilent regular w/	35 CaCl. Volume of	comment always the on. It
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer		to time, or	sensor orman so	on plant 60%. Bette	mated formation temp.
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer	7	SERVICE PRO	Rey of comes a	7777 yar aquare inch	. Camera was in place
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer	a ttoil		Productions	4 a #ksa#	
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer	A STATE OF	of Labbara		and a large, community	t W150 ox Portant regul
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer	4 2000	N 00 8-1/0	The same of	and the latest land by	me berere test, bested (
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer	200 an	Portland me	1 m m/m mi	and a solid and an	State a 2334-70, customen
pany PACIFIC ECREMENT PIPELIES CORPORATION PACIFIC ECREMENT PIPELIES CORPORATION Tess Promingion, New Munice By Griginal Signed by Goo. 2. Poppin Title District Provetion Engineer	hare best	ore test, an	secured to broad	· held off.	· Ammer was the Street
PACIFIC NUMBER PREMILIES CORPORATION ress					
PACIFIC NUMBER PIPELINE CORPORATION ress					
PACIFIC NUMBER PIPELINE CORPORATION ress	understand •	hat this plan of work	must persion annual !	iting by the Castantast Communication	
ress hill West Breaduny By Griginal signed by Goo. 2. Poppin Title District Provetion Engineer	4	has the plan of work			s operations may be commenced.
Parmington, Nov Newles By Criginal signed by Geo. 2. Poppin Title District Provetion Engineer	npany	MODATE BORT	Mary Paralles C		
Parmington, Nov Newles By Griginal signed by Geo. 2. Poppis Title District Provetion Engineer	ress	ide Hest Bre	e-Guey		
Title District Provetion Ingineer		Paradacton. 1	lev Nuntee	- Outstant	nimed by Sec. 9 Seeds
• • • • • • • • • • • • • • • • • • •				-	
GPO 9 18 507				Title	Properties suffered.
					GPO 9 18 507

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Land Office Charte To

1 - State Land Office 1 - L. G. Truby 1 - File (SUBMIT

(SUBMIT IN TRIPLICATE)

Form 9-381 a. (Feb. 1951)