(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

UNITED STATES 7 DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	SUBSEQUENT REPORT OF WATER SHUT-OFF	x
OTICE OF INTENTION TO DRILL	AT SUBSTING OF ACIDITING	
TICE OF INTENTION TO CHANGE PLANS	TEDING CASING	
TICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF REPUBLIS OR PEPAIR	
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF THE STATE OF	
OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF TEXAS	
DTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO ABANDON WELL		
		**
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	· ·	10 69
	April 30,	, 17 .3 4
	om. $\{S\}$ line and $\{S\}$ line of second $\{S\}$ line of $\{S\}$	C
/4 SW/4 Sec.7 29 Forth	(Range) (Meridian)	
(1/2 Sec. and Sec. 140.)	Nev Mexico	
(Count	ty or Subdivision) (State or Territory)	
(Field)		
ne elevation of the decided above sea	level is 6493.2 ft.	
he elevation of the	WAS OF WORK	
DET.	AILS OF WORK	~ iohs cemen
and expected depths to objective sands; show	v sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work)	g jobs, cerner
Spudded 4-4-57. Set 222.18' of 10 1/2% CeCl.)-3/4" casing € 236'; cemeated v/200 r	sx reg
Spudded 4-4-57. Set 222.18' of 10 1/2% CeCl.)-3/4" casing € 236'; cemeated v/200 r	sx reg
Spudded 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing @ 37	1-3/4" casing @ 236'; cemented w/200 r	ex sec
Spudded 4-4-57. Set 222.18' of 10 1/2% CeCl. Set 3687.25' of 7-5/8" casing @ 37	1-3/h" casing @ 236'; cemented w/200 m 700', cemented w/150 ax w/8% gel & 50	ex sec
guided 4-4-57. Set 222.18° of 10 1/2% CeCl. Set 3687.25° of 7-5/8" casing € 37	1-3/h" casing @ 236'; cemented w/200 m 700', cemented w/150 ax w/8% gel & 50	ex sec
spudded 4-4-57. Set 222.18' of 10 1/2% CeCl. Set 3687.25' of 7-5/8" casing @ 37	1-3/h" casing @ 236'; cemented w/200 m 700', cemented w/150 ax w/8% gel & 50	ex sec
Spudded 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing @ 37	1-3/h" casing @ 236'; cemented w/200 m 700', cemented w/150 ax w/8% gel & 50	ex sec
Spudded 4-4-57. Set 222.18' of 10 1/2% CeCl. Set 3687.25' of 7-5/8" casing @ 37	1-3/h" casing @ 236'; cemented w/200 m 700', cemented w/150 ax w/8% gel & 50	ex sec
spudded 4-4-57. Set 222.18' of 10 1/2% CeCl. Set 3687.25' of 7-5/8" casing @ 37	1-3/h" casing @ 236'; cemented w/200 m 700', cemented w/150 ax w/8% gel & 50	ex sec
Spudded 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing @ 37 3et 2215.23' of 5-1/2" liner @ 580 1/20 sx reg. Tested top liner w/	1-3/h" casing @ 236'; commanded w/200 m 1/00', commented w/150 ax w/8% gel & 50 1/00', Bassh Ross Liner Hanger @ 3501.7 1/2500f press, held ok.	ex sec
guided 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing € 37 Set 2215.23' of 5-1/2" liner € 580 1/150 sx reg. Tested top liner w/	1-3/h" casing @ 236'; commanded w/200 m 1/00', commented w/150 ax w/8% gel & 50 1/00', Bassh Ross Liner Hanger @ 3501.7 1/2500f press, held ok.	ex sec
Set 3687.25° of 7-5/8" casing @ 37 Set 2215.23° of 5-1/2" liner @ 580 v/150 sx reg. Tested top liner w/	1-3/h" casing @ 236'; cemented w/200 1 100', cemented w/150 ax w/85 gel & 50 100', Bassh Ross Liner Hanger @ 3504.7 12500 press, held ok.	ex sec
pudded 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing @ 37 Set 2215.23' of 5-1/2" liner @ 580 1/150 sx reg. Tested top liner w/	1-3/h" casing @ 236'; commanded w/200 m 1/00', commented w/150 ax w/8% gel & 50 1/00', Bassh Ross Liner Hanger @ 3501.7 1/2500f press, held ok.	ex sec
Spudded 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing © 37 3et 2215.23' of 5-1/2" liner © 580 1/20 sx reg. Tested top liner w/	1-3/h" casing @ 236'; cemented w/200 1 100', cemented w/150 ax w/85 gel & 50 100', Bassh Ross Liner Hanger @ 3504.7 12500 press, held ok.	ex sec
Junderstand that this plan of work must receive approve Company PACIFIC NOTICE 1. Set 222.18' of 10 provided 4-4-57. Set	1-3/h" casing @ 236'; cemented w/200 1 100', cemented w/150 ax w/85 gel & 50 100', Bassh Ross Liner Hanger @ 3504.7 12500 press, held ok.	ex sec
pudded 4-4-57. Set 222.18' of 10 1/2% CaCl. Set 3687.25' of 7-5/8" casing @ 37 Set 2215.23' of 5-1/2" liner @ 580 1/150 sx reg. Tested top liner w/	1-3/h" casing @ 236'; cemented w/200 m 100', cemented w/150 ax w/84 gel & 50 100', Bassh Ross Liner Hanger @ 3501.7 12500f press, held ok.	ex sec
pudded 4-4-57. Set 222.18' of 10 /2% CaCl. Set 3687.25' of 7-5/8" casing @ 37 Set 2215.23' of 5-1/2" liner @ 580 /150 sx reg. Tested top liner w/	1-3/h" casing @ 236'; cemented w/200 1 100', cemented w/150 ax w/85 gel & 50 100', Bassh Ross Liner Hanger @ 3504.7 12500 press, held ok.	ex sec