



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-B358.4
Approval expires 12-31-60.

Land Office New Mexico
Lease No. 531
Unit San Juan 29-5 Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	RECEIVED NOV 23 1959
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO
NOV 23 1959

Well No. 2-1-50 is located 250 ft. from N line and 25 ft. from E line of sec. 1
2-1-50 (1/4 Sec. and Sec. No.) 25 (Twp.) 1 (Range) 1 (Meridian)
San Juan Co. (Field) San Juan Co. (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3595 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 11-15-59 Total Depth 7608'.
 Run 75 joints 7", 238, 4-80 casing (2342') and 169 joints 7", 438, 3055 casing (5312'), for total of 244 joints (7674') set at 7606' w/475 sacks cement, 475 sacks regular cement w/1/4 Floerite and 6% Cal, 1/2 tuffplug.

Hold 1000/30 minutes.

Top of cement by temperature survey at 3596'.

UV tool at 3596'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company San Juan Petroleum Co. Inc.

Address Box 507
Farmington, New Mexico

By ORIGINAL SIGNATURE D.H. MEARS

Title Regional Engineer