

District I
P.O. Box 1980, Hobbs, NM
District II
P.O. Drawer DD, Artesia, NM 88211
District III
1000 Rio Brazos Rd, Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

SUBMIT 1 COPY TO
APPROPRIATE
DISTRICT OFFICE
AND 1 COPY TO
SANTA FE OFFICE

Lenny E. Font
DEPUTY OIL & GAS INSPECTOR

SEP 15 1995

PIT REMEDIATION AND CLOSURE REPORT

Operator: Phillips Petroleum Company **Telephone:** (505) 599-3460
Address: 5525 Hwy. 64, NBU 3004, Farmington, NM 87401
Facility Or: San Juan 29-6 Unit #64
Well Name _____
Location: Unit or Qtr/Qtr Sec SW NE Sec 9 T 29N R 6W County Rio Arriba
Pit Type: Separator X Dehydrator _____ Other Condensate Tank
Land Type: BLM X, State _____, Fee _____, Other _____

Pit Location: Pit dimensions: length 22', width 22', depth 4.5'
(Attach diagram)
Reference: wellhead X, other _____
Footage from reference: 45
Direction from reference: 20 Degrees X East North X
of
_____ West South _____

Depth To Ground Water: 60'
(Vertical distance from
contaminants to seasonal
high water elevation of
ground water)

Less than 50 feet	(20 points)
<u>X</u> 50 feet to 99 feet	(10 points)
Greater than 100 feet	(0 Points) <u>10</u>

Wellhead Protection Area:
(Less than 200 feet from a private
domestic water source, or; less than
1000 feet from all other water sources)

Yes	(20 points)
<u>X</u> No	(0 points) <u>0</u>

Distance To Surface Water:
(Horizontal distance to perennial
lakes, ponds, rivers, streams, creeks,
irrigation canals and ditches)

Less than 200 feet	(20 points)
200 feet to 1000 feet	(10 points)
<u>X</u> Greater than 1000 feet	(0 points) <u>0</u>

RANKING SCORE (TOTAL POINTS): 10

PHILLIPS PETROLEUM PIT ASSESSMENT SUMMARY
REVISED DATE: JANUARY 7, 1994

1993/1994

ENVIROTECH, INC.

REC

PIT NO.	WELL NAME	U-S-T-R	PIT TYPE	RANK SCORE	CLOSURE STANDARD TPH (PPM)	DATE 93/04	GROUNDWATER MONITORING Sub-Surf Depth	SOIL TYPE	PIT TYPE	SAMPLE NO.	Organic Vapor Meter (PPM)	Total Recoverable Per. Hydro. (PPM)	EPA METHOD 8020 (PPB) METHOD 5030 PURGE - AND - TRAP					STATUS
													Benzene	Toluene	Ethyl Benzene	Xylene	TOTAL BTEX	
PA108	SAN JUAN 20-6, #94	G092006	SEP	10	1000	1-3	NO	OL	EARTHEN	T1-5 T1-7.5	0 0	0						CLOSE
PA109	SAN JUAN 20-6, #29	N032006	SEP	0	5000	1-3	NO	OL	EARTHEN	T1-5 T1-7.5	41.3 1.1	0						CLOSE
PA110	SAN JUAN 20-6, #102	G102006	SEP	0	5000	1-3	NO	OL/SM	EARTHEN	T1-4.5 T1-7	42 1.1	0						CLOSE
PA111	SAN JUAN 20-6, #32	L112006	SEP	0	5000	1-3	NO	OL	EARTHEN	T1-4.5 T1-7	0 1.1	0						CLOSE
PA112	SAN JUAN 20-6, #99	M112006	SEP	20	100	1-3	NO	SM	EARTHEN	T1-5 T2-5	277 13.2	9600 22						REM
PA113	SAN JUAN 20-6, #17	A012006	SEP	10	1000	1-3	NO	OL	EARTHEN	T1-5 T1-7.5	12 927	110	18200	60100	16400	42000	136700	REM/TEST
PA114	SAN JUAN 20-6, #111	C012006	SEP	0	5000	1-4	NO	SM	EARTHEN	T1-4 T2-5	1845 1236	5400 12	0	110	0	235.7	354.7	REM
PA115	SAN JUAN 20-6, #92	M122006	SEP	10	1000	1-4	NO	OL	EARTHEN	T1-4 T1-6.5	20 45	20						CLOSE
PA116	SAN JUAN 20-6, #33 DK	A132006	SEP	10	1000	1-4	NO	OL	EARTHEN	T1-5	32	0						CLOSE
PA117	SAN JUAN 20-6, #33 MV	A132006	SEP	10	1000	1-4	NO	OL	EARTHEN	T1-4.5 T1-7	2 233	16	0	104	16.1	300	420.1	CLOSE
PA118	SAN JUAN 20-6, #90	H152006	SEP	10	1000	1-4	NO	CL	EARTHEN	T1-4.5 T1-7	1.2 2.5	10						CLOSE
PA119	SAN JUAN 20-6, #14A	I072006	SEP	0	5000	1-4	NO	CL	EARTHEN	T1-6 T1-11 T1-17 T2-5 T2-10 T2-16	1049 2131 1752 12 324 2077	10000 350 12 12 450	1200 4920 63100	31500 8200	3550 6200	49100 74600	85410 151020	REM/TEST
PA120	SAN JUAN 20-6, #12A	J082006	SEP	10	1000	1-5	NO	CL	EARTHEN	T1-6 T1-11 T1-16 T2-5 T2-10 T2-16	1000 1425 717 990 87 272	8100 6800 310 12 12	338	12900	1890	37400	52628	REM
PA121	SAN JUAN 20-6, #13A	D082006	SEP	10	1000	1-5	NO	CL	EARTHEN	T1-4.5 T1-9.5 T1-17 T2-5 T2-10 T2-16	869 830 863 0 3 2	2900 2000 920	52	3500	324	9930	13800	REM
PA122	SAN JUAN 20-6, #81	L252006	SEP	0	5000	1-5	NO	SM/ML	EARTHEN	T1-5 T1-10	549 452	13400 2000	0	105	0	264	360	REM
PA123	SAN JUAN 20-6, #91	H212006	SEP	0	5000	1-6	NO	SP/CL	EARTHEN	T1-4 T1-6.5	339 2.6	10	34.6	85	0	35.9	155.5	CLOSE
PA124	SAN JUAN 20-6, #11A	D072006	SEP	0	5000	1-6	NO	SM	EARTHEN	T1-4.5 T1-7	828 849	2000	2130	58400	6300	71300	136130	REM/TEST

DATE: _____

FIT NO. PA102

C.C. No.

JCE No: 93163
PAGE No 1 of 1

PROJECT: PIT ASSESSMENT
CLIENT: PHILLIPS PETROLEUM
CONTRACTOR: ENVIROTECH, INC.
EQUIPMENT USED: CASE EXTEND-A-DIG

DATE STARTED: 1-3-90
DATE FINISHED: 1-3-90
ENVIRO. SPCLT. REF
OPERATOR: CIMARRON
ASSISTANT: K.C.

LOCATION: LEASE: SAN JUAN 29-6 WELL: * 64-9 QD: 1450' N, 2250' E (G)
SEC: 9 TWP: 29 N RNG: 6 W PM: NM CNTY: R.A. ST: NM PIT: SEP

LAND USE: RANGE - LEASE # SF 080377

SURFACE CONDITIONS: EARTHEN PIT - FENCED 22' x 22' - NO SURFACE STAIN

FIELD NOTES & REMARKS: PIT IS LOCATED APPROXIMATELY 45 FEET N. 20° E OF WELLHEAD.

CLOSURE STD: 1000 AM TTH

TL: moist brown granitic silty sand - no odor.

RANKING SCORE: 10

[illegible]

4 x 2 = 8. GAC # 0346.

RECOMMEND PIT CLOSURE.

TEST FOR 1990:

[illegible]

SOIL TYPE: C - Clay, M - Silt, S - Sand, G - Gravel Plasticity: L - None, H - Plastic Grading: 0 - Poorly, 1 - Med.

SCALE



0 10 20 FEET

SITE DIAGRAM

