

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FNL, 1650' FEL, Sec. 4, T-29-N, R-7-W, NMPM

5. Lease Number
SF-078945

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
San Juan 29-7 Unit
San Juan 29-7 U #82

9. API Well No.
30-039-07671

10. Field and Pool
Fulcher Kutz PC/
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

12-22-98 MIRU. SD for holiday.
12-28-98 ND WH. NU BOP. TOOH w/2 3/8" tbg. TIH w/CIBP, set @ 4750'. Load hole w/2% KCl wtr. TOOH. TIH, ran CBL-CCL-GR @ 3500-4750', TOC @ 3784'. TOOH. SDON.
12-29-98 TIH w/4 1/2" csg spear. Chemical cut 4 1/2" csg @ 3782'. TOOH w/88 jts 4 1/2" csg. TIH w/6 1/4" swedge. Work swedge over lnr top @ 3782'. TOOH w/swedge. TIH w/7" RBP, set @ 3190'. Ran CBL-CCL-GR @ 0-3190', TOC @ 250', 100% bond over Pictured Cliffs interval @ 2990-3190'. TOOH. SDON.
12-30-98 TIH w/pkr, set @ 3001'. PT RBP to 3000 psi/30 min, OK. TOOH w/pkr. TIH, perf Pictured Cliffs w/2 SPF @ 3065-3125' 26 holes total. Acidize w/24 bbl 15% HCL. Frac Pictured Cliffs w/525 bbl 20# linear gel, 135,000# 20/40 Brady sd, 625,000 SCF N2. CO after frac.
12-31-98 Blow well & CO.
1-1-99 Blow well & CO.
1-2-99 Blow well & CO. TIH w/retrieving tool to RBP @ 3190'. Blow well & CO.
1-3/6-99 Blow well & CO.
1-7-99 Blow well & CO. TOOH. TIH w/7" Model "32A" pkr, set @ 2986'. Load hole w/2% KCL wtr. PT csg to 500 psi, failed. Establish injection into csg failure. TOOH w/pkr. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 1/27/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations or any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE

1-8-99 TIH, ran tracer survey on Pictured Cliffs interval. TOOH. TIH w/7" RBP, set @ 2986'. TIH w/pkr, PT RBP to 1000 psi, OK. Release pkr. Blow well & CO. Dump 20' sd on RBP. Isolate csg leaks @ 100-120', 120-1600', 1600-1682'. TOOH. SDON.
 1-9-99 TIH, perf 2 sqz holes @ 1690'. TOOH. TIH w/7" pkr, set @ 1500'. Establish injection. Release pkr, TOOH. TIH, pump 80 sx Class "B" neat cmt @ 1315-1730'. TOOH. TIH w/7" pkr, set @ 250'. Pump 80 sx Class "B" neat cmt w/2% calcium chloride @ 1550-1690'. Reset pkr @ 50'. Perf 2 sqz holes @ 100'. Pump 50 sx Class "B" neat cmt w/2% calcium chloride into perfs @ 100'. Circ 2 bbl cmt to surface. Sqz to 800 psi. WOC. SD for Sunday.
 1-11-99 Release pkr, TOOH. TIH w/bit, tag TOC @ 71'. Drill cmt @ 71-97'. PT sqz holes @ 85' to 800 psi/30 min, OK. TOOH. TIH, tag TOC @ 1506'. Drill cmt @ 1506-1770'. Load hole w/50 bbl 2% KCl wtr. PT sqz holes @ 85', 1550-1690' to 800 psi/30 min, OK. TIH to 2974'.
 1-12-99 CO sd on top of RBP @ 2986'. TOOH. TIH w/7" retrieving tool. Load hole w/60 bbl 2% KCL wtr. Release RBP, TOOH. TIH w/7" retrieving tool to 3160'. Blow well & CO.
 1-13-99 Blow well & CO.
 1-14-99 Blow well & CO. Latch RBP @ 3190', TOOH. TIH w/3 7/8" mill to CIBP @ 4750'. Establish circ. Mill out CIBP. Circ hole clean to 5686'.
 1-15-99 Blow well & CO. TOOH. TIH w/7" Model "D" pkr, set @ 3190'. TIH w/180 jts 2 3/8" 4.7# J-55 EUE tbg & seal assembly. Land tbg @ 5629'. SDON.
 1-16-99 TIH w/96 jts 1 1/2" 2.76# J-55 IJ tbg, landed @ 3132'. Blow well & CO. ND BOP. NU WH. RD. Rig released.