


5- 1500
1- L.G. Truby
1- File (SUBMIT IN TRIPLICATE)



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 87 077736

Unit 29-4
114-00-002-1033

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Sub report of well Completion</u>	<u>1</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 24, 1936, 19__

Well No. 11-6 is located 1040 ft. from [S] line and 1005 ft. from [E] line of sec. 6

SE 1/4 SE 1/4 6 20N 4E 100W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

PC Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the Ungrated Ground above sea level is 7338.5 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 4595', and perf 4484-4532 w/3 shots/ft and 4532-42' w/2 shots/ft. Free PC w/29,400 gals water and 30,000' 20-40 sd. BD 2000', avg 1100', max 1200', final 1000', stdg 100', in 5 min. IR 30 BPM. Perf. 4396-4466', w/2 shots/ft and free PC w/ 31,900 gals water and 30,000' 20-40 sd. BD 1200', avg 1200', max and final 1200', stdg 90' in 15 min. IR 30 BPM. Perf 4314-44', w/2 shots /ft. and free PC w/31,900 gals water and 30,000' 20-40 sd. BD 1000', avg 1200', max and final 1200', stdg 200', in 15 min. IR 45 BPM. Perf 4280-24' w/3 shots/ft and free PC w/31,900 gals water and 30,000' 20-40 sd. BD 1400', avg 1100', max 1400', final 1300', stdg 400' in 15 min IR 45.2 BPM. Cleaned out to total depth, set tubing and released rig 7:00 AM, 9-8-36.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pacific Northwest Pipeline Corp.

Address 4051 N. Broadway

Farmington, New Mexico

By

Title District Engineer

