NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122 Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Poo	1 <u>R</u> 1	anco			I	Formation	Hesa.	Verde		_County_	Rio Arr	iba	
Ini	tial_			Annu	ai		Spec	ial		_Date of	Test_6	/7/57	
Com	pany_	maific	Horti	west.	Pipeli	ne	Lease	29-5		Wel	l No	19-6	, <u>, , , , , , , , , , , , , , , , , , </u>
Uni	t		Sec. 🐔	Tw	ر ش	298 Rg	e. 5 W	Purc	haser_ Ic	t Connect	ed		
Cas	7 ing_ 5	5/8 1	/t	I	.D	Se	3950 t at 601.0) Pe:	rf. 5936	t Connect	To	550	5
													2
										ell Singl			
Date	e o.f 0	omplet	ion:		_	Packe	r	Sin	gle-Brade Reservo	enhead-G. oir Temp.	G. or	3.0. D	ual
		_	_					ED DATA					
Test	ted Th	rough	(16123		Choke)	(MESTE)				Туре Тар			
				Flow D		7		Tubing	Dat a	Casing D			
N.		over)	(Cho	oke)		. Diff.	Temp.			Press.		1	Ouration
No.		ine) ize		fice) ize	psig	h _w	o _F .	psig	o _F .	psig	°F∙		of Flow Hr.
SI 1.			3/		285		65	892 285	65	1128	i .		3
2.			- 3 /	<u> </u>	200			207					<u></u>
3 . 4.			1								<u> </u>	ļ	
5.					 	+							
No.			Pressure		- ,		Gravity Factor	Compress. Factor Fpv		· -			
1.	14.1605					297	.9952		.9608			4134	
2. 3.												·	
4.													
as I	Liquid	Hydro Liqui		ocarbo			cf/bbldeg.		Speci Speci	fic Gravi fic Gravi 11 40	ty Flow	ring Fl	
No.	P _w	psia)	Pt	F	.Q	$(F_cQ)^2$	(F (1	cQ) ² -e-s)	874 P _w 2	$P_c^2 - P_w^2$	Ca	l.	Pw Pc
I. 2.									763.9	535.7			2.43
3.										· · · · · · · · · · · · · · · · · · ·			
1. 2. 3.											<u> </u>		
COMF ADDF AGEN WITN	PANY RESS	TITLE	.Jorti		Pipeli	ne Carpa	ration	n75/	1.	9462	AFEE	957	
JOH	AN 1.			······ · ···			REM	ARKS		10	IL CON	. COM	1

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 600 F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_{w} Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}\mbox{\footnotesize =}\mbox{\footnotesize Differential meter pressure, inches water.}$
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

OIL CONSERVATION COMMISSION									
AZTEC DISTRICT OFFICE									
No. Copies Received 3									
DISTRIBUTION									
	FUP ISHED	1							
Operator	3.11.0								
Santa Fe	/								
Proration Office									
State Land Office									
U. S. G S.	/								
Transporter									
File		V							