Form	9-331
May	1963
·	

UNITED STATES SUBMIT IN TRIPLICATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-UNITED STATES

Form approved. Budget Bureau No. 42-R.424, 5. LEASE DESIGNATION AND SERIAL NO.

NM-2992

	GEOLOGICAL SURVEY					
SHNDRY	NOTICES	ΔND	REPORTS	ON	WELL	ς

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

(Do not use this form for proposals to drill or to deepen or plug back to a different rese Use "APPLICATION FOR PERMIT—" for such proposals.)	rvoir.
OIL GAS WELL OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Aztec Oil & Gas Company	Arrowhead
3. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Drawer 570, Farmington, New Mexico	#1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.	10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface	Blanco Mesaverde
915' FLN & 810' FEL, Section 3-29N-5W	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Section 3=29N-5W
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GE, etc.)	12. COUNTY OR PARISH 13. STATE
6858' GR	San Juan New Mexico
16. Check Appropriate Box To Indicate Nature of Notice R	eport or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:						
TEST WATER SHUT-OFF		PULL OR ALTER CASING	_	-		WATER SHUT-OFF		REPAIRING WELL	
FRACTURE TREAT SHOOT OR ACIDIZE		MULTIPLE COMPLETE ABANDON*		· -		SHOOTING OR ACIDIZING		ALTERING CASING ABANDONMENT®	\overline{x}
REPAIR WELL (Other)	<u> </u>	CHANGE PLANS			<u> </u>	(Other) (Note: Report resul Completion or Recon	lts of multiple apletion Report	completion on Wel and Log form.)	<u></u>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) •

6-1-72 Moved in, rigged up.

6-2-72 Ran 10 jts of 8-5/8", 24# casing, set at 330.80'. Cement circulated. (225 sxs)

6-15-72 T.D. 6145'. Ran ES-Induction and Gamma Density logs.

0-16-72 Set cement plugs at 5800 to 5650 with 43 sxs class "A", 3850 to 3750 with 43 sxs class "A", 3150 to 2950 with 58 sxs class "A", 350 to 300 with 155 sxs class "A", 10 sxs at surface with dry hole marker. Cleaned location.

QUIS. GEOLOGICAL SU WEY DURANGO, COLO.



18. , hereby certify that the foregoing is true and correct			
GNED Jue C Balmer	TITLE _	District Superintendent	DATE June 20, 1072
(This space for Federal or State office use)			
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE _		DATE