Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

(5 1110 177 07	NI OF THE INTERIOR	Expires: March 31, 1993
BUREAU OF	LAND MANAGEMENT	5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS		SF-078278
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR	R PERMIT - " for such proposals	
SURMI	T IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well		 San Juan 29-6 Unit
Oil X Gas Well Other		8. Well Name and No.
2. Name of Operator		SJ 29-6 Unit #34A
Phillips Petroleum Company 3. Address and Telephone No.		9. API Well No.
5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454		30-039-21122
4. Location of Well (Footage, Sec., T., R., M., or Survey		10. Field and Pool, or exploratory Area
Unit I, 1840' FSL & 910' FEL		Blanco Mesaverde
Section 14, T29N, R6W		11. County or Parish, State
		Rio Arriba, NM
12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPORT	, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	L
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Add pay & stimulate	Dispose Water (Note: Report results of multiple completion on Well
2. Proposite Proposed on Completed Operations (Charles to		Completion or Recompletion Report and Log form.)
give subsurface locations and measured and true ve	ill pertinent details, and give pertinent dates, including estimated date of star rtical depths for all markers and zones pertinent to this work.)*	ting any proposed work. If well is directionally drill
See the attached for details of th	e procedure used to add Lewis Shale pay to t	he existing Mesaverde
formation and stimulate.		
		9, 9
		010 to 10 to
		함 그 연변
	5 5 6 7	
	DECENVER	
		9 7
	UU DEC - 1 1997 E	THE PH 1: 16
	Q00 000 000	
	@الل @@NJ. D[[V]	>
	DIST. 3	
14. I hereby certify that the foregoing is true and corpect	/	
Signed Talsy (lugi	Regulatory Assistant	Date 11-17-97
(This space for Federal or State office use)	Ţ,	TEPTED FOR RECORD
Approved by	Title	Date
Conditions of approval, if any:		NOV 26 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

San Juan 29-6 #34A SF-078278; Unit I, 1840' FSL & 910' FEL Section 14, T29N, R6W; Rio Arriba County, NM

Details of procedure to add Lewis Shale pay to existing MV & stimulate.

11/8/97

MIRU Big A #29. Killed well. ND WH & NU BOPS. Change out BOPs. PT - OK. Pull BPV. COOH w/tubing. RIH w/bit & scraper & run to 5900'. POOH. RU BJ & set RBP @ 5365'. Dumped 10 gal. sand on top of BP. RIH w/open ended tubing. Fill hole w/2% KCL H₂O. PT - plug, casing & rams to 500 psi for 30 min. OK. POOH.

RU Blue Jet & ran GR/CCL/CBL log from 5350' - 3400'. RU to perf Lewis Shale @ 1 spf (.38" holes).

```
5293' - 5298' (5'); 5213' - 5218' (5'); 5082' - 5087' (5');

4982' - 4987' (5'); 4910' - 4915' (5'); 4788' - 4793' (5');

4718' - 4723' (5'); 4650' - 4655' (5'); 4545' - 4550' (5');

4486' - 4491' (5'); 4456' - 4461' (5'); 4418' - 4423' (5') Total 60 holes
```

RIH & set 4 ½" FB Packer @ 4170'. RU BJ to acidize. Pumped 1500 gal 15% HCl & 60 ballsealers. RIH & retrieved 59 ballsealers. RIH & set packer @ 3480'. PT annulus - OK. RIH w/RTD & set 4565'. RU to frac. BJ pumped w/91,370 gal of 60 Quality N_2 foam consisting of 43,344 gal of X-link 30# gel & 1.26 mmscf N_2 gas. Pumped 302,500 # 20/40 Brady sand. Avg. rate - 59 bpm & avg. treating pressure 3300 psi. ISDP 500 psi. Flowed back immediately on ¼" choke for approx. 36 hours.

RD frac head. Retrieved & COOH w/RTD tool. Ran audio log across perfs. RIH & cleaned out to RBP and retrieved. RIH w/2-3/8" J-55 and N-80 tubing. Cleaned out hole to 6115'. Landed tubing @ 6066'. ND BOPs & NU WH. Pull BPV. RD & released 11/16/97. Turned well over to production departement.