STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting

	paction leakage tests In Southeast New Mexico NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST									
Opt.2.3	yan Frodu	uction Corp. Lesse Sherman Ed Well 2								
Location of Well: Unit	Sec. 3	TWD. 29N	Rge	<u>5W</u>		county <u>RA</u>				
0	TYPE OF PROD. (Oil or Gos)		METHOD OF P (Flow or Art		PROD. MEDIUM (Thy. or Cog.)					
Upper Completion	6		Flow		76					
Lower Completion	The state of the s			Ges 7l		low 1 bg				
	_	PRE-FLO	W SHUT-IN PI	SI press pale	ATA	Stabilized 2 Mag	~ 1101			
Upper Hour, date Completion; 0',4'	- 4	360	Stabilized? (Yes							
1	Lower Hour, date shut-in			SI press. polg		No				
Companies O, 4.	3 00 10 10	<u> </u>	FLOW TEST	NO. 1						
Commenced at Piour, d	ele)* 10;30 c	10.2093	TLOW ILDI.		cing (Upper or Lower):	Upper				
TIME	LAPSED TIME	PRESSI	URE Lower Completion	PROD. ZO		REMARK	REMARKS			
(frour, date)	SINCE*	Upper Completion	//\							
10:45a 10.21-9	3 / day	330	<u> </u>							
10:45, 10-2-9	1 4	330	Ø							
						FIS CE	ALL SERVICES			
				<u> </u>			-3-1 93 4			
		<u> </u>		<u></u>		<u> </u>	No TONIVA			
Production rate	during test		·			DIST	L 3			
Oil:	BOF	D based on	Bbls. in		Hours.	_ Grav	GOR			
Gas:	20) MCFF	D; Tested thru	(Orifice or	Meter): Mo	ker	.,			
U43			ST SHUT-IN PI							
May date	shul-in	MLD-1E		SI press. poig		Stabilized? (Yes	Stabilized? (Yes or No)			
Upper Completion:						Stabilized? (Yes	or Naj			
Lower Completion			H a	Si press. peig						

FLOW TEST NO. 2

des Sieses er Les

Commenced at New, det	16) * *			Tom broading fabr			
TIME flour, dotal	LAPSED TIME	Upper Campieties	Lewer Completion	PROD. ZONE TEMP.	REMARKS		
, sam				1			
				<u> </u>			
	1		i	:	:		
			1				
		 		1	And and an arranged from the second of the s		
					• • • •		
					i		
			ļ				
Production rate d	-	D based on	Bbls. i	n Hours.	Grav	GOR	
G25·		мсі	PD: Tested thr	ı (Orifice or Meter):		
·							
Remarks:		· <u></u>			 		
					_		
I hereby certify th	at the informat	ion herein contain	ed is true and c	omplete to the bes	t of my knowledge.		
. 1		994		_	n Froduction Cor	Λ.	
				<i>D</i> A '	-11 1 1	•	
New Mexico Of	il Conservation	Division		By Xulu	u Standardt		
A C	// L	(1) []			_		
Ву	arles S	hotson		Title Prod.	type. Supuse		
DEPUT	TY OIL & GAS IN	ispector, dist. 🖇	3	Date 11-10	-93		
Title				Date			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is so be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minuse intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil sames only).