Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATES DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved, Budget Bureau No. 42-R1424. 5. WELL DESIGNATION AND BERIAL NO.

-	6. IF INDIAN, ALLOTTER OR TRIBE NAME							
	6.	IF	INDIAN,	ALLOTTEE	OR	TRIBE	NAME	

GEOLOGICAL SURVEY						
SUNDRY	NOTICES	AND	REPORTS	ON WELLS		

Oo not use this form for y	oroposals to drill or to deepen or plug back to a different reservoir. PLICATION FOR PERMIT—" for such proposals.)				
1.		7. UNIT AGREEMENT NA	ME		
OIL GAS X OTH	ER	San Juan 29-6	Unit		
2. NAME OF OPERATOR		8. FARM OR LEASE NAM	Е		
Northwest Pipelin	ne Corporation	San Juan 29-6	Unit		
3. ADDRESS OF OPERATOR		9. WELL NO.			
P.O. Box 90 Far	mington, New Meixco 87401	6A			
4. LOCATION OF WELL (Report locat See also space 17 below.)	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*				
At surface		Blanco Mesa Verde			
1095	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA				
	Sec. 21, T29N	, R6W			
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE		
	6400' CR	Rio Arriba	N.M.		

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16.

ROTICE OF INTENTION TO.			Sobbagonii in to the			
· · · · ·						
TEST WATER SHUT-OFF	PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL		
FRACTURE TREAT	MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING		
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*		
REPAIR WELL	CHANGE PLANS		(Other)			
(Other)			(Note: Report results of m Completion or Recompletion	altiple completion on Well Report and Log form.)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-21-76 MOL & RU. Spud at 4:00 AM. Drilled 13 3/4" hole to 225'. Ran 5 jts. (208') 9 5/8", 36#, K-55 casing set at 225'. Cemented with 180 sxs. C1. "B" w/1/4#gel flake/sx and 3% CC. Cement circulated. WOC

7-22-76 Tested casing and BOP's to 600 PSI for 30 minutes, held OK.



18. I hereby certify that the foregoing is true and correct SIGNED	TITLE _	Production Engineer	DATE	7/27/76
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE _	,	DATE	