

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____						5. LEASE DESIGNATION AND SERIAL NO. SF 078284											
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____						6. IF INDIAN, ALLOTTEE OR TRIBE NAME											
2. NAME OF OPERATOR Northwest Pipeline Corporation						7. UNIT AGREEMENT NAME San Juan 29-6 Unit											
3. ADDRESS OF OPERATOR P.O. Box 90, Farmington, New Mexico 87401						8. FARM OR LEASE NAME San Juan 29-6 Unit											
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1180' FNL & 1650' FWL At top prod. interval reported below As above At total depth As above						9. WELL NO. 27A											
14. PERMIT NO. _____ DATE ISSUED _____						10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde											
15. DATE SPUDDED 4-14-77 16. DATE T.D. REACHED 4-19-77 17. DATE COMPL. (Ready to prod.) 4-29-77 18. ELEVATIONS (DF, REB, RT, GR, ETC.)* 6448' GR 19. ELEV. CASINGHEAD						11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 23, T29N, R6W											
20. TOTAL DEPTH, MD & TVD 5746' 21. PLUG, BACK T.D., MD & TVD 5707' 22. IF MULTIPLE COMPL., HOW MANY* _____ 23. INTERVALS DRILLED BY _____ ROTARY TOOLS A11 CABLE TOOLS						12. COUNTY OR PARISH Rio Arriba 13. STATE N.M.											
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 5146' to 5638' Mesa Verde						25. WAS DIRECTIONAL SURVEY MADE No											
26. TYPE ELECTRIC AND OTHER LOGS RUN GR-Neutron						27. WAS WELL CORED No											
28. CASING RECORD (Report all strings set in well)																	
CASING SIZE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED							
9 5/8"		32.3		194'		12 1/4"		125 sks.									
7"		20		3750'		8 3/4"		150 sks.									
29. LINER RECORD												30. TUBING RECORD					
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*		SCREEN (MD)		SIZE		DEPTH SET (MD)		PACKER SET (MD)			
4 1/2"		3602'		5742'		210				2 3/8"		5645'		None			
31. PERFORATION RECORD (Interval, size and number) One shot at: 5146', 5158', 5188', 5196', 5204', 5210', 5264', 5272', 5328', 5334', 5482', 5492', 5536', 5544', 5552', 5560', 5566', 5576', 5582', 5596', 5606', 5614', 5622', 5630', 5638'. Size: 0.32" holes								32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.									
								DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED							
								5146' - 5638'		1500 gal. 7 1/2% HCl. Fraced with 60,000# 20/40 sand and 70,000 gal. slick water.							
33.* PRODUCTION																	
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing						WELL STATUS (Producing or shut-in) Shut-in									
DATE OF TEST		HOURS TESTED		CHOKE SIZE		PROD'N. FOR TEST PERIOD		OIL—BBL.		GAS—MCF.		WATER—BBL.		GAS-OIL RATIO			
4-29-77		3		48/64		→				CV-4664							
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HOUR RATE		OIL—BBL.		GAS—MCF.		WATER—BBL.		OIL GRAVITY-API (CORR.)					
296 PSIG		589 PSIG		→				AOF 8496									
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Waiting on pipeline connection														TEST WITNESSED BY			
35. LIST OF ATTACHMENTS																	
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records																	
SIGNED		D.H. Maroncelli						TITLE				Sr. Drilling Engineer		DATE		5/4/77	

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions. If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Mesa Verde	5131'		SS. Buff to light gray, silty in part, fine to medium grained, interbedded with siltstone, shale and coal.	Ojo Alamo	2518'	Same
				Kirtland	2649'	"
				Fruitland	3100'	"
				Pictured Cliffs	3395'	"
				Lewis	3550'	"
				Cliff House	5131'	"
				Menefee	5208'	"
				Point Lookout	5524'	"
				T.D.	5746'	"