

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

JOHN E. SCHALK

3. ADDRESS OF OPERATOR

P. O. BOX 25825/ ALBUQUERQUE, NM 87125

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1170' FSL, 950' FWL  
AT SURFACE: Sec. 25, T-29N, R-4W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Drilling ☒

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

SEP 11 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/26/80 Spud and Drill 12-1/4" Surface hole to 312'  
8/27/80 Ran 7 jts. 8-5/8" 32# K-55 Casing. Set @ 310.05 KBM  
Cement with 225 sxs. Class 'B' 2% c.c. Plug down @  
5:00 a.m.  
8/31/80 thru 9/5/80. Cored internal from 4020 - 4366'. Recovered  
a total of 271' core.  
9/6/80 Circulate for logs 4:15 p.m.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Managing Partner DATE 9/9/80

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

FARMINGTON DISTRICT

BY [Signature]

\*See Instructions on Reverse Side