

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
JOHN E. SCHALK
3. ADDRESS OF OPERATOR  
P. O. BOX 25825
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1740' FSL; 1560' FWL; SEC. 26, AT SURFACE: Township 29N, R4W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) DRILLING	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE	NM-18325
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	-----
7. UNIT AGREEMENT NAME	-----
8. FARM OR LEASE NAME	Schalk 29-4
9. WELL NO.	# 7
10. FIELD OR WILDCAT NAME	Gobernador Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Sec. 26, T-29N, R-4W
12. COUNTY OR PARISH	13. STATE
Rio Arriba	New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD)	7060' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5/23/79 Set 107 joints 10.5#; 4-1/2" casing @ 4360'. Cemented with 200 sxs. 50-50 Posmix, 2% Gel (7# Salt & 12-1/2# Gilsonite per sx.)

Float @ 4308'

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John E. Schalk TITLE OPERATOR DATE May 25, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

\*See Instructions on Reverse Side

RECEIVED  
MAY 30 1979

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.