Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

5. Lease Serial No. NMSF078917

| Do not use this<br>abandoned wel  | 6. If Indian, Allottee or Tribe Name                   |   |                                 |  |                  |  |
|---|--|---|---------------------------------|--|------------------|--|
| SUBMIT IN TRII  | 7. If Unit or CA/Agreement, Name and/or No. NMNM78415B |   |                                 |  |                  |  |
| Type of Well  |  |   |                                 | 8. Well Name and No.<br>SJ 29-5 91         |                  |  |
| 2. Name of Operator Contact: PHILLIPS PETROLEUM COMPANY   |  | PATSY/CLUGSTON E-Mail: plclugs@ppco.com                             |                                 | 9. API Well No.<br>30-039-21786-00-S1      |                  |  |
| 3a. Address<br>5525 HIGHWAY 64 NBU 3004<br>FARMINGTON., NM 87401  |  | 3b. Phone No. (include area code) Ph: 505.599.3454 Fx: 505-599-3442 |                                 | 10. Field and Pool, or Exploratory UNNAMED |                  |  |
| 4. Location of Well (Footage, Sec., T.  |  |   | 11. County or Parish, and State |  |                  |  |
| Sec 35 T29N R5W NWNE 114<br>36.68610 N Lat, 107.32367 W   |  |   | RIO ARRIBA COUNTY, NM           |  |                  |  |
| 12. CHECK APPR  | ROPRIATE BOX(ES) TO                                    | O INDICATE NATURE OF 1  | NOTICE, R                       | EPORT, OR OTHE                             | R DATA           |  |
| TYPE OF SUBMISSION  | TYPE OF ACTION   |   |                                 |  |                  |  |
| ☐ Notice of Intent  | ☐ Acidize  | ☐ Deepen ☐ Pro  |                                 | tion (Start/Resume)                        | ☐ Water Shut-Off |  |
|   | ☐ Alter Casing   | ☐ Fracture Treat ☐ Reclar   |                                 | nation                                     | ■ Well Integrity |  |
| Subsequent Report     ■     Subsequent Report     Subsequent Report | ☐ Casing Repair  | ☐ New Construction  | Recom                           | plete                                      | Other            |  |
| ☐ Final Abandonment Notice  | ☐ Change Plans   | ☐ Plug and Abandon ☐ Temp   |                                 | rarily Abandon                             |                  |  |
| <b> </b>  | Convert to Injection                                   | n Plug Back Water   |                                 | ·  |                  |  |
| 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once to the involved operation. The property Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has  |  |   |                                 |  |                  |  |

PROCEDURE USED TO ADD THE MV INTERVAL TO THIS WELL. THE DK INTERVAL PREVIOUSLY P&A'd.

7/17/02 WSI changed out WH to 5000#. PT casing to 3600 psi. Good test. RU Blue Jet & perforated Mesaverde interval @ 1 spf .34" holes - 6898', 6853', 6836', 6761', 6753', 6743', 6722', 6689', 6675', 6665', 6648', 6634', 6625', 6523', 6518', 6442', 6432', 6316', 6310', 6301' total 20 holes. Acidized perfs w/1500 gal 15% HCL. RU to frac. Pumped 82,237 gal 60 Quality Slickwater foam and 74,300# 20/40 Brown Sand. Flowed back on 1/4" and 1/2" chokes.

determined that the site is ready for final inspection.)

7/25/02 RU Blue Jet & BJ. RIH & set CIBP @ 6000'. PT-OK. Perf'd Lewis Shale @ 1 spf .34" holes -5739', 5725', 5709', 5691', 5673', 5650', 5623', 5608', 5598', 5590', 5520', 5482', 5471', 5457', 5445', 5249', 5234', 5220', 5211', 5195', - 20 holes total. RU BJ - pumped 69,000 gal X-linked 30# gel 60 Quality N2 foam w/200,200# 20/40 Brown sand. Flowed back on 1/4" and 1/2" chokes. Sl.

| 14. I hereby certify that the foregoing is true and correct.  Electronic Submission #13101 verified by the BLM Well Information System  For PHILLIPS PETROLEUM COMPANY, sent to the Farmington  Committed to AFMSS for processing by Matthew Halbert on 08/23/2002 (02SXM0432SE) |                         |            |  |  |  |  |  |
|--|-------------------------|------------|--|--|--|--|--|
| Name (Printed/Typed)   | PATSY CLUGSTON          |            | Title AUTHORIZED REPRESENTATIVE                          |  |  |  |  |
| Signature  | (Electronic Submission) | Date       |  |  |  |  |  |
| THIS SPACE FOR FEDERAL OR STATE OFFICE USE   |                         |            |  |  |  |  |  |
|  | ACCEPTED                |            | MATTHEW HALBERT Title PETROLEUM ENGINEER Date 08/23/2002 |  |  |  |  |
| _Approved By   | <u></u>                 | — <u> </u> | Tido   |  |  |  |  |
| Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.                        |                         | ,          | Office Farmington  |  |  |  |  |

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Additional data for EC transaction #13101 that would not fit on the form

## 32. Additional remarks, continued

8/15/02 MIRU Key #29. Kill well w/40 bbls 2% KCI. ND frac valve & NU BOP. PT-OK. RIH w/mill & C/O fill to CIBP @ 6000'. D/O CIBP. C/O to PBTD @ 7290' (top of final DK P&A plug). COOH. RIH w/2-3/8", 4.7# tubing and set @ 6892' with "F" nipple set @ 6884'. ND BOP, NU WH. Pumped off exp. check. RD & released rig 8/19/02. Turned well over to production department to put back on line as MV well only.