

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0558139

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Creek

9. WELL NO.

#1A

10. FIELD AND POOL, OR WILDCAT

Blanco MV
Gobernador PC

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 4, T29N, R5W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

870' FWL & 800' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6634' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Perforation and Stimulation

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-7-79 Perforated the Point Lookout at: 5737', 5743', 5800', 5806', 5812', 5824', 5830' and 5836'. Total of 8 holes. Brokedown with 600 gallons of 15% HCl and balls. Fracd with 67,000 gallons of water and 62,000# of 20/40 sand. ATP 1250, AIR 14, ISIP 0.

9-8-79 Set retrievable bridge plug on wireline at 5680'. Perforated the Cliff House at 5502', 5507', 5518', 5532', 5547', 5609', 5619', 5625', 5631', 5641', 5647' & 5653'. Total of 12 holes. Brokedown with 900 gallons of 15% HCl and balls. Fracd with 71,000 gallons of water and 66,000 # of 20/40 sand. ATP 2500, AIR 22, ISIP 1000. Set retrievable bridge plug at 3750'. Perforated the Pictured Cliffs at: 3452', 3460', 3468', 3476', 3484', 3492', 3500', 3566', 3572', 3578', 3586', 3594', 3602', 3610', 3618', 3626', 3634', 3642', 3650' & 3658'. Total of 20 holes. Brokedown with 1500 gallons of 15% HCl and balls. Fracd with 174,500 gallons of water and 172,500# of 20/40 sand. ATP 2000, AIR 36, ISIP 800.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager

DATE 9-10-79

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

SEP 12 1979

*See Instructions on Reverse Side