30-039-22091

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	BURLINGTON RESOURCE	ES OIL & GAS CO.		Lease	CREEK			Well No.	1A
Location	Unit P Sect	04 Twp.	029N	Dao	005W	County	RIO ARRIBA		
of Well:		RESERVOIR OR POOL		Rge.	YPE OF PROD.	<u>_</u>	OD OF PROD.	PRC	D. MEDIUM
	NAME OF	RESERVOIR OR FOOL	•	'	(Oil or Gas)	i	v or Art. Lift)		bg. or Csg.)
Upper Completion	PICTURED CLIFFS				Gas	ı	Flow		Tubing
Lower Completion	MESAVERDE				Gas	ı	Flow		Tubing
		PRE-F	LOW SHUT-IN	PRESS	URE DATA				
Upper	Hour, date shut-in Length of time shut-in			SI press. psig Stabilized? (Y				s or No)	
Completion	4/16/98	6/98 96 Hours			422				
Lower Completion	4/16/98	144 Hours			249				
			FLOW TES	T NO.					
	at (hour,date)*	4/20/98			J 7			PER	
TIME	LAPSED TIME		SSURE		PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Completion		TEMP	REMARKS			
4/21/98	120 Hours	331	331 249			turned on upper zone, lower zone blind plate			
4/22/98	144 Hours	331	249			upper zone flowed 107 mcf			
			N	匡(Per	zone flowed 67	mcf, low	er zone still bli
<u> </u>				JU	W 1 9 1998	ש			
					ON. DI	177			
				[9]	1517. 33	ψ ₀			
Production rate	during test					- - - .			
Oil:	BOPD based on	PD based on Bbls. in		Hours.	Hours. Grav.		GOR		
Gas:		MCFPD; Tested thru (0	Orifice or Meter):						
		, m	omer all et Di	222500	Y TO A TO A				
	TT To the state in		TEST SHUT-IN	,			OLL Hands (V.	Na	
Upper Completion	Hour, date shut-in	Length of time shut-in		SI p	ress. psig	Stabilized? (Yes or No)			
Lower Completion	Hour, date shut-in	Length of time shut-in		SI p	SI press. psig		Stabilized? (Yes or No)		

(Continue on reverse side)

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

New Mexico Oil Conservation Division

Title

By Deputy Oil & Gas Inscention

Operator

B. Palary Sta

Title _

Date <u>6/17/98</u>

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 5 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours terms: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day terms: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Attec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).